



ASSOCIATION CONNECTING
ELECTRONICS INDUSTRIES®



IPC-1710A

OEM Standard for Printed Circuit Board Manufacturer's Qualification Profile For:

Multilayer Technology
3835 Conflans Road
Irving, Texas 75061
972-790-0062 PH
972-790-0293 FAX

Website: www.multilayer.com

Sales: sales@multilayer.com

AS9100C & ISO9001:2008 Certified

MIL-PRF-55110 Certified

GIN (Polyimide) 4101/42 & GFN (FR4) 4101/24

Types 1,2 & 3 w/certified etchback

Developed by the OEM council of the IPC, the MQP sets the standard for assessing PWB manufacturers capabilities and allows PWB manufacturers to more easily satisfy customer requirements.

IPC-1710A

A standard developed by IPC

2215 Sanders Rd, Northbrook, IL 60062-6135

Tel. 847.509.9700 Fax 847.509.9798

www.ipc.org

NOTICE

IPC standards and publications are designed to serve the public interest through eliminating misunderstandings between manufacturers and purchasers, facilitating interchangeability and improvement of products, and assisting the purchaser in selecting and obtaining with minimum delay the proper product for his particular need. Existence of such Standards and Publications shall not in any respect preclude any member or non-member of IPC from manufacturing or selling products not conforming to such Standards and Publications, nor shall the existence of such Standards and Publications preclude their voluntary use by those other than IPC members, whether the standard is to be used either domestically or internationally.

Recommended Standards and Publications are adopted by IPC without regard to whether their adoption may involve patents on articles, materials or processes. By such action, IPC does not assume any liability to any patent owner, nor do they assume any obligation whatever to parties adopting the recommended Standard or Publication. Users are also wholly responsible for protecting themselves against all claims of liabilities for patent infringement.

The material in this standard was developed by the OEM Council of the Institute for Interconnecting and Packaging Electronic Circuits.

FOREWORD

It is not intended that this Manufacturers' Qualification Profile (MQP) satisfies all the requirements of the customer, however, conscientious maintenance of this document and or registration to ISO 9000 requirements should satisfy the major concerns. Thus, audits should be simpler, required less frequently, and facilitate less paper work as customers and suppliers work closer to meeting each others needs.

ACKNOWLEDGMENTS

The IPC is indebted to the members of the OEM council who participated in the development of this document. A note of thanks is also expressed to the members of the IPC Presidents Council for their review and critique and construction recommendations in finalizing the principles developed for the MQP.

Although the IPC is grateful for all the involvement and individual contributions made in completing the MQP a special acknowledgment is extended to the following individuals. It was their dedication and foresight that made this publication possible.

| | | | |
|--|--|--|--|
| Rudolfo Archbold <i>Digital Equipment Corp</i> | Rick Iantaffi <i>Northern Telecom</i> | Don Noel <i>Harris Corp. - Computer Sys. Div</i> | Mario Suarez-Solis <i>Encore Computer Corp.</i> |
| Patrick Bernardi <i>IBM</i> | Sue Jones <i>Wilcox Electric</i> | Rick Smith <i>Compaq Computer Corp.</i> | Gordon Wolfram <i>Raytheon Company</i> |
| Vernon Brown <i>Motorola, Inc.</i> | Chuck Krzesicki <i>Honeywell Avionics Division</i> | Peter Solecky <i>IBM</i> | Jerald G. Rosser <i>Hughes Missile Operations Div.</i> |
| Don Holt <i>Texas Instruments</i> | Thomas Kurtz <i>Hughes Defense Communications</i> | Joseph F. Sterba <i>Honeywell, Inc.</i> | Jamie Zanos <i>Wellborn Industries Ltd.</i> |

CONTENTS

| <u>Sections:</u> | <u>Pages:</u> |
|---------------------------------------|---------------|
| 1.1 Company Description | 1 |
| 1.2 Site Description | 2 |
| 2.1 Process | 3-4 |
| 2.2 Electrical Test Equipment | 5-7 |
| 2.3 Product Type | 8-10 |
| 2.4 Product Complexity | 11-14 |
| 2.5 Quality Development | 15-16 |
| 3.0 Equipment Profile | 17-21 |
| Master Equipment Listing | 22 |
| 4.0 Technology Profile Specifics | 23-30 |
| 5.0 Quality Profile | 31-41 |
| 6.0 Manufacturing History | 42 |
| 7.0 Identification of Previous Audits | 43 |
| 8.0 Financial Review | 44 |
| 9.0 MQP Electronic Editing | 45 |

SECTION 1.1

COMPANY DESCRIPTION

DATE COMPLETED

10/27/2016

| GENERAL INFORMATION | | | |
|--|---|--|--|
| LEGAL NAME Multilayer Technology | | | |
| PHYSICAL ADDRESS 3835 Conflans Road | | | |
| CITY Irving | STATE Texas | ZIP 75061 | |
| PROVINCE N/A | COUNTRY USA | | |
| TELEPHONE NUMBER 972-790-0062 | FAX NUMBER 972-790-0293 | TELEX NUMBER N/A | |
| E-MAIL ADDRESS sales@multilayer.com | MODEM NUMBER Replaced with FTP feature | DATE FOUNDED 1986 <input type="checkbox"/> PUBLIC <input checked="" type="checkbox"/> PRIVATE | |
| INTERNET URL www.multilayer.com | FTP SITE Call for FTP setup (Secured) | | |

| MANAGEMENT |
|--|
| PRESIDENT Viny Mulani |
| EXECUTIVE VICE PRESIDENT Naren Tarpara |
| VICE PRESIDENT OF MANUFACTURING Bharat Chodavadia |
| DIRECTOR OF QUALITY ASSURANCE Alan Cochrane |
| DIRECTOR OF SALES Johnnie Feathers |
| PRODUCTION MANAGER Juan Rubio |
| PLANNING ENGINEERING Jimmy Mathis |

| CORPORATE DESCRIPTION | NUMBER OF EMPLOYEES | | COMMENTS |
|---------------------------------|---------------------|------|--------------------------------------|
| | CORPORATE | SITE | |
| DESIGN AND DEVELOPMENT | 1 | | |
| ENGINEERING (PLANNING/CAM) | 5 | | |
| MANUFACTURING MANAGER/SUP | 4 | | |
| MANUFACTURING | DIRECT | 28 | |
| | INDIRECT | 3 | |
| QUALITY CONTROL | QUALITY ENGINEERS | 1 | |
| | INTERNAL AUDITORS | 4 | |
| | INSPECTORS | 4 | |
| TOP MANAGEMENT & ADMINISTRATION | 7 | | |
| TOTAL | 51 | | Some personnel may have dual duties. |

SECTION 1.2

SITE DESCRIPTION

(TO BE COMPLETED FOR EACH SITE)

DATE COMPLETED 10/27/2016
ATTACH APPROPRIATE CHARTS (OPTIONAL)

MANUFACTURING FACILITY

| | | | |
|--|----------------------|--|------------------------------|
| COMPANY NAME | | Multilayer Technology | |
| PHYSICAL ADDRESS | | 3835 Conflans Road | |
| CITY | Irving | STATE | Texas |
| PROVINCE | N/A | COUNTRY | USA |
| TELEPHONE NUMBER | 972-790-0062 | FAX NUMBER | 972-790-0293 |
| E-MAIL ADDRESS | sales@multilayer.com | MODEM NUMBER | Replaced with FTP feature |
| | | YEARS IN BUSINESS | 25 |
| INTERNET URL | www.multilayer.com | FTP | Call for FTP setup (Secured) |
| PRINCIPLE PRODUCTS/SERVICES/SPECIALTIES | | BUSINESS CHARACTERIZATION (HIGH VOLUME, QUICK TURN-AROUND, ETC.) | |
| Manufacturer of high quality PCB's, AS9100C, ISO2001:2008, MIL-PRF-55110, ITAR | | Quantities ranging from prototypes to medium production volumes, 24 hrs to 4 weeks leadtime available. | |

FACILITY MANAGEMENT

TITLE

REPORTS TO (Function/Job Title)

| | | |
|---|-------------------------------|---------------------|
| OVERALL OPERATION RESPONSIBILITY FOR THIS SITE Bharat Chodavadia | VP of Manufacturing | President |
| PRESIDENT Viny Mulani | President | President |
| PLANNING ENGINEERING Jimmy Mathis | Planning/Process Engineering | Production Manager |
| PRODUCTION MANAGER Juan Rubio | Production Manager | VP of Manufacturing |
| PURCHASING Kelli Cain | Office/Purchasing Manager | President |
| DIRECTOR OF QUALITY ASSURANCE Alan Cochrane | Director of Quality Assurance | President |
| DIRECTOR OF SALES Johnnie Feathers | Director of Sales | President |
| PRODUCTION PROCESS ENGINEERING Juan Rubio | Process Engineering Manager | Production Manager |

BUILDINGS

SYSTEMS (INDICATE % COVERAGE)

| | AGE | AREA (Sq. Ft.) | Construction (Wood/Brick) | Power Conditioning | Heating | Ventilation | Air Conditioning | Sprinklers | Waste Treatment | Other |
|-------------------|-------|----------------|---------------------------|--------------------|---------|-------------|------------------|------------|-----------------|-------|
| Office | 16 | 2000 | BRK/MTL | 100 | 100 | 100 | 100 | 100 | 0 | |
| Manufacturing | 16/25 | 23000 | BRK/MTL | 100 | 100 | 100 | 100 | 100 | 100 | |
| Storage | 5 | 4000 | BRK | 0/100 | 0/100 | 100 | 0/100 | 0 | 0 | |
| Planned additions | DEV | 60,000 | BRK/MTL | 100 | 100 | 100 | 100 | 100 | 75 | |

SAFETY AND REGULATORY AGENCY REQUIREMENTS

| | | | | |
|--|---|--|---|---|
| Are fire extinguishers functional and accessible to employees? | <input checked="" type="checkbox"/> YES | <input type="checkbox"/> NO | What is the distance to the nearest fire station? (in minutes) | 3 Minutes |
| Do you conform to local/federal environment protection agency requirements? | <input checked="" type="checkbox"/> YES | <input type="checkbox"/> NO | Date of last OSHA visit | 1994 |
| | | | Date of last EPA visit | 1998 |
| Are you currently operating under a waiver or in violation of local government requirements? | <input type="checkbox"/> YES | <input checked="" type="checkbox"/> NO | Other Agency Audits, AS9100, UL, ISO 9001:2008, NECQ, CSA Approval and Number | <input checked="" type="checkbox"/> UL # e97097 <input type="checkbox"/> CSA # _____ |
| | | | | <input checked="" type="checkbox"/> ISO 9000# 9001:2008 <input checked="" type="checkbox"/> Other AS9100 C & MIL-PRF-55110 |
| Do you have a safety program? Describe below. | <input checked="" type="checkbox"/> YES | <input type="checkbox"/> NO | Hazardous Waste Number | |
| | | | Trade Waste Account Number | |

PLANT PERSONNEL (TOTAL EMPLOYEES)

| Regular | Contract | Office | Technical/Engineering | Production | Full-Time QA | Part-Time QA | Union | Non-Union | Union Name | Contract Expires (Date) |
|---------|----------|--------|-----------------------|------------|--------------|--------------|-------|-----------|------------|-------------------------|
| 8 | 0 | 2 | 5 | 30 | 6 | 0 | N/A | ALL | N/A | N/A |

| |
|--|
| |
| |

SECTION 2.1

PROCESS

DATE COMPLETED

10/27/16

This section is intended to provide overview information on the processes used to fabricate printed board products.

Site Capability Snapshot (Please Check all that apply)

| Designators | | Remarks |
|-------------|---|----------------------------------|
| A | Conductor Forming Processes <input checked="" type="checkbox"/> Subtractive <input checked="" type="checkbox"/> Thin Foil Subtractive less than .5 oz. <input type="checkbox"/> Semi-Additive <input checked="" type="checkbox"/> Additive (Electro-less) <input type="checkbox"/> Black Hole <input type="checkbox"/> Thick Film Paste and Fire <input type="checkbox"/> Thin Film Semi-conductor Sputtering <input type="checkbox"/> Other: | Copper Reduction down to <1/8 oz |
| B | PTH Materials and Processes <input checked="" type="checkbox"/> Acid Copper <input type="checkbox"/> Pyro-Phosphate Copper <input type="checkbox"/> Full Built Electro-Less <input type="checkbox"/> Gold Paste <input checked="" type="checkbox"/> Copper Paste <input type="checkbox"/> Gold Conductor Sputtering <input type="checkbox"/> Nickel Conductor Sputtering <input checked="" type="checkbox"/> Other: Silver Fill Paste | High Impingment Pulse Plate |
| C | Permanent Over-plating <input checked="" type="checkbox"/> Tin (Immersion White Tin) <input checked="" type="checkbox"/> Tin-Lead (HASL 60/40) <input checked="" type="checkbox"/> ENIG (Electroless Nickel Immersion Gold) <input checked="" type="checkbox"/> Soft Wire Bondable Gold <input checked="" type="checkbox"/> Nickel Gold (Hard) (Electro Plated) <input checked="" type="checkbox"/> Nickel Gold (Soft) (Wire Bondable Gold) <input checked="" type="checkbox"/> Nickel Palladium Gold (Electro Plated) <input checked="" type="checkbox"/> Conductive Polymer <input checked="" type="checkbox"/> Other: Immersion Silver, ENEPIG and Lead-Free HAL. | |

IPC-1710A

| | | | |
|---|-----------------------------|---|--|
| D | Permanent Selective Plating | <input checked="" type="checkbox"/> Tin (Immersion White Tin) <input checked="" type="checkbox"/> Tin-Lead (HASL 60/40) <input checked="" type="checkbox"/> Soft Wire Bondable Gold <input checked="" type="checkbox"/> ENIG (Electroless Nickel Immersion Gold) <input checked="" type="checkbox"/> Nickel Gold (Hard) (Electro Plated) <input checked="" type="checkbox"/> Nickel Gold (Soft) (Wire Bondable Gold) <input type="checkbox"/> Nickel Palladium Gold (Electro Plated) <input checked="" type="checkbox"/> Other: Immersion Silver, ENEPIG and Lead-Free HAL. | |
| E | Permanent Mask or Coating | <input checked="" type="checkbox"/> Photo Dry Film <input checked="" type="checkbox"/> Photo Liquid <input checked="" type="checkbox"/> Image Transfer Screen Mask <input checked="" type="checkbox"/> Conformal Coating Solder Mask <input checked="" type="checkbox"/> Cover Coat <input type="checkbox"/> Other: | |
| F | Other Surface Finishes | <input checked="" type="checkbox"/> Tin-Lead Fused <input checked="" type="checkbox"/> Immersion Tin <input checked="" type="checkbox"/> Solder Leveled <input type="checkbox"/> Roll Soldered <input type="checkbox"/> Electro-less Solder Fused <input checked="" type="checkbox"/> Solder Bumped Lands <input type="checkbox"/> Solder Paste Fused <input checked="" type="checkbox"/> Azole Organic Protective Covering <input type="checkbox"/> Flux Protective Covering <input checked="" type="checkbox"/> Other: Lead-Free HAL, Soft Wire Bondable Gold. Ni-Pd-Au, ENEPIG. | <p>Currently not used</p> <p>Outsourcerd</p> |

SECTION 2.2

ELECTRICAL TEST EQUIPMENT

| |
|------------------------------|
| DATE COMPLETED 10/27/2016 |
|------------------------------|

This section is intended to provide overview information on the test equipment and testing capability of the manufacturer.

Site Capability Snapshot (Please Check the column that applies furthest to the right.)

| Designators | | | Remarks |
|-------------|-------------------|---|---------|
| A | Number of Nets | <input type="checkbox"/> <200 <input type="checkbox"/> 200 <input type="checkbox"/> 500 <input type="checkbox"/> 1000 <input type="checkbox"/> 2000 <input type="checkbox"/> 3000 <input type="checkbox"/> 4000 <input type="checkbox"/> 5000 <input checked="" type="checkbox"/> >5000 <input type="checkbox"/> Other: | |
| B | Number of Nodes | <input type="checkbox"/> <500 <input type="checkbox"/> 500 <input type="checkbox"/> 1000 <input type="checkbox"/> 2000 <input type="checkbox"/> 3000 <input type="checkbox"/> 4000 <input type="checkbox"/> 5000 <input type="checkbox"/> 6000 <input checked="" type="checkbox"/> >6000 <input type="checkbox"/> Other: | |
| C | Probe Point Pitch | <input type="checkbox"/> >1.0 [.040] <input type="checkbox"/> 1.0 [.040] <input type="checkbox"/> 0.8 [.032] <input type="checkbox"/> 0.65 [.025] <input type="checkbox"/> 0.50 [.020] <input type="checkbox"/> 0.40 [.016] <input type="checkbox"/> 0.30 [.012] <input type="checkbox"/> 0.20 [.008] <input checked="" type="checkbox"/> <0.20 [.008] <input type="checkbox"/> Other: | |

IPC-1710A

| | | | |
|---|----------------------|---|--------------|
| D | Test % Single Pass | <input type="checkbox"/> None <input type="checkbox"/> <60% <input type="checkbox"/> 60% <input type="checkbox"/> 70% <input type="checkbox"/> 80% <input type="checkbox"/> 90% <input checked="" type="checkbox"/> 95% <input type="checkbox"/> 99% <input type="checkbox"/> 100% <input type="checkbox"/> Other: | |
| E | Probe Accuracy (DTP) | <input type="checkbox"/> >0.2 [.008] <input type="checkbox"/> 0.2 [.008] <input type="checkbox"/> 0.15 [.006] <input type="checkbox"/> 0.125 [.005] <input type="checkbox"/> 0.1 [.004] <input type="checkbox"/> 0.075 [.003] <input checked="" type="checkbox"/> <0.075 [.003] <input type="checkbox"/> Other: | |
| F | Grid Density | <input checked="" type="checkbox"/> Single Side Grid <input checked="" type="checkbox"/> Double Sided Grid <input checked="" type="checkbox"/> Double Density Grid <input checked="" type="checkbox"/> Double Density Double Sided <input type="checkbox"/> Quad Density <input type="checkbox"/> Double Sided Quad Density <input checked="" type="checkbox"/> Flying Probe <input type="checkbox"/> Other: | |
| G | Netlist Capability | <input type="checkbox"/> Golden Board <input checked="" type="checkbox"/> IPC-D-356 <input checked="" type="checkbox"/> Net List Extraction <input checked="" type="checkbox"/> CAD/CAM Net List Compare <input type="checkbox"/> Other: | No long used |

| | | | |
|---|---------------------|---|--|
| H | Test Voltage | <input type="checkbox"/> <20 VDC <input type="checkbox"/> 20 VDC <input type="checkbox"/> 40 VDC <input type="checkbox"/> 60 VDC <input type="checkbox"/> 80 VDC <input type="checkbox"/> 100 VDC <input type="checkbox"/> 500 VDC <input checked="" type="checkbox"/> 1000 VDC <input type="checkbox"/> >1000 VDC <input type="checkbox"/> Other: | |
| J | Impedance Meas | <input checked="" type="checkbox"/> Micro Section <input checked="" type="checkbox"/> Inboard Circuit <input checked="" type="checkbox"/> Coupon <input checked="" type="checkbox"/> Manual TDR <input type="checkbox"/> Automated TDR <input checked="" type="checkbox"/> Other: Semi-Automated (Polar Instruments) | |
| K | Impedance Tolerance | <input type="checkbox"/> None <input type="checkbox"/> >20% <input type="checkbox"/> 20% <input type="checkbox"/> 15% <input checked="" type="checkbox"/> 10% <input checked="" type="checkbox"/> 7% <input checked="" type="checkbox"/> 5% <input type="checkbox"/> 2% <input type="checkbox"/> <2% <input type="checkbox"/> Other: | |

SECTION 2.3

PRODUCT TYPE

| |
|------------------------------|
| DATE COMPLETED 10/27/2016 |
|------------------------------|

This section is intended to provide overview information on the printed board product types being fabricated by the manufacturer.

Site Capability Snapshot (Please Check all that apply.)

| Designators | | Remarks |
|-------------|-----------------------|---|
| A | Product Type | <input checked="" type="checkbox"/> Rigid Printed Board <input checked="" type="checkbox"/> Flex Printed Board <input checked="" type="checkbox"/> Rigid/Flex Board <input checked="" type="checkbox"/> Rigid Back Plane <input type="checkbox"/> Molded Product <input checked="" type="checkbox"/> Ceramic Printed Board <input type="checkbox"/> Multichip Module <input type="checkbox"/> Laminated Multichip Module <input type="checkbox"/> Deposited Dielectric Multichip Modules <input checked="" type="checkbox"/> Other: Metal backing / Heatsink |
| B | Circuit Mounting Type | <input checked="" type="checkbox"/> Single Sided <input checked="" type="checkbox"/> Double Sided <input checked="" type="checkbox"/> Multilayer <input checked="" type="checkbox"/> Single-sided Bonded to Substrate <input checked="" type="checkbox"/> Double-sided Bonded to Substrate <input checked="" type="checkbox"/> Multilayer Bonded to Substrate <input checked="" type="checkbox"/> Constrained Multilayer <input type="checkbox"/> Distributed Plane Multilayer <input type="checkbox"/> Other: |
| C | Via Technology | <input checked="" type="checkbox"/> No-Vias <input checked="" type="checkbox"/> Thru Hole Vias <input checked="" type="checkbox"/> Buried Vias <input checked="" type="checkbox"/> Blind Vias <input checked="" type="checkbox"/> Thru Hole & Blind Vias <input checked="" type="checkbox"/> Thru Hole & Buried Vias <input checked="" type="checkbox"/> Thru Hole Buried & Blind Vias <input checked="" type="checkbox"/> Buried & Blind Vias <input checked="" type="checkbox"/> Other: Conductive & non-conductive materials |

| | | | |
|---|------------------------|---|--|
| D | Laminate Material | <input type="checkbox"/> Phenolic <input type="checkbox"/> Epoxy Paper <input checked="" type="checkbox"/> Epoxy Glass <input checked="" type="checkbox"/> Modified Epoxy Composite <input checked="" type="checkbox"/> Polyimide Film & Reinforce <input checked="" type="checkbox"/> Cyanate Ester <input checked="" type="checkbox"/> Teflon <input checked="" type="checkbox"/> Ceramic Glass Types <input checked="" type="checkbox"/> Various Combinations <input checked="" type="checkbox"/> Other: flex materials | |
| E | Core Material | <input type="checkbox"/> No Core <input type="checkbox"/> Polymer <input checked="" type="checkbox"/> Copper <input checked="" type="checkbox"/> Aluminum <input type="checkbox"/> Graphite <input type="checkbox"/> Copper Invar/Copper <input type="checkbox"/> Copper Moly/Copper <input checked="" type="checkbox"/> Other: Brass, Aluminum, copper. | |
| F | Copper Thickness (Oz.) | <input type="checkbox"/> 1/8 Minimum <input checked="" type="checkbox"/> 1/4 Minimum <input checked="" type="checkbox"/> 3/8 Minimum <input checked="" type="checkbox"/> 1/2 Nominal <input checked="" type="checkbox"/> 1 Nominal <input checked="" type="checkbox"/> 2 Nominal <input checked="" type="checkbox"/> 3-5 Max <input type="checkbox"/> 6-9 Max <input type="checkbox"/> >10 <input type="checkbox"/> Other: | |
| G | Construction | <input checked="" type="checkbox"/> ≤4 Planes <input checked="" type="checkbox"/> >4 Planes <input checked="" type="checkbox"/> THK to TOL ≤0.2 mm <input type="checkbox"/> THK to TOL >0.2 mm <input checked="" type="checkbox"/> Bow/Twist ≤1% <input type="checkbox"/> Bow/Twist >1% <input checked="" type="checkbox"/> ≤0.3 mm Profile Tolerance <input type="checkbox"/> 0.3 mm Profile Tolerance <input type="checkbox"/> Other: | |

IPC-1710A

| | | | |
|---|-----------------------|--|--|
| H | Coatings and Markings | <input checked="" type="checkbox"/> ≤ 0.1 mm Mask Clearance <input type="checkbox"/> > 0.1 mm Mask Clearance <input checked="" type="checkbox"/> One Side (Legend) <input checked="" type="checkbox"/> Two Side (Legend) <input checked="" type="checkbox"/> None (Legend) <input checked="" type="checkbox"/> UL Material Logo <input checked="" type="checkbox"/> U.L. V ₀ Logo <input checked="" type="checkbox"/> U.L. V ₁ Logo <input checked="" type="checkbox"/> U.L. V ₂ Logo <input type="checkbox"/> Other: | |
|---|-----------------------|--|--|

SECTION 2.4

PRODUCT COMPLEXITY

| |
|------------------------------|
| DATE COMPLETED 10/27/2016 |
|------------------------------|

This section is intended to provide overview information on product complexity being fabricated by the manufacturer.

(Please check the column that applies farthest to the right)

| Designators | | | Remarks |
|-------------|--------------------------|--|---------|
| A | Board Size Diagonal | <input type="checkbox"/> <250 [10.00] <input type="checkbox"/> 250 [10.00] <input type="checkbox"/> 350 [14.00] <input type="checkbox"/> 450 [17.50] <input type="checkbox"/> 550 [21.50] <input type="checkbox"/> 650 [25.50] <input checked="" type="checkbox"/> 750 [29.50] <input type="checkbox"/> 850 [33.50] <input type="checkbox"/> >850 [33.50] <input type="checkbox"/> Other: | |
| B | Total Board Thickness | <input type="checkbox"/> 1,0 [.040] <input type="checkbox"/> 1,0 [.040] <input type="checkbox"/> 1,6 [.060] <input type="checkbox"/> 2,0 [.080] <input type="checkbox"/> 2,5 [.100] <input type="checkbox"/> 3,5 [.135] <input type="checkbox"/> 5,0 [.200] <input type="checkbox"/> 6,5 [.250] <input checked="" type="checkbox"/> >6,5 [.250] <input type="checkbox"/> Other: | |
| C | Number Conductive Layers | <input type="checkbox"/> 1-4 <input type="checkbox"/> 5-6 <input type="checkbox"/> 7-8 <input type="checkbox"/> 9-12 <input type="checkbox"/> 13-16 <input type="checkbox"/> 17-20 <input type="checkbox"/> 21-24 <input type="checkbox"/> 25-28 <input checked="" type="checkbox"/> >28 <input checked="" type="checkbox"/> Other: Up to 44 layers | |

IPC-1710A

| | | | |
|---|--------------------------------|---|--|
| D | Dia Drilled Holes | <input type="checkbox"/> >0,5 [.020] <input type="checkbox"/> 0,5 [.020] <input type="checkbox"/> 0,4 [.016] <input type="checkbox"/> 0,35 [.014] <input type="checkbox"/> 0,30 [.012] <input type="checkbox"/> 0,25 [.010] <input type="checkbox"/> 0,20 [.008] <input checked="" type="checkbox"/> 0,15 [.006] <input type="checkbox"/> <0,15 [.006] <input type="checkbox"/> Other: | |
| E | Total PTH TOL (Max-Min) | <input type="checkbox"/> >0,250 [.010] <input type="checkbox"/> 0,250 [.010] <input type="checkbox"/> 0,200 [.008] <input type="checkbox"/> 0,150 [.006] <input type="checkbox"/> 0,125 [.005] <input type="checkbox"/> 0,100 [.004] <input type="checkbox"/> 0,075 [.003] <input type="checkbox"/> 0,050 [.002] <input checked="" type="checkbox"/> <0,050 [.002] <input type="checkbox"/> Other: | |
| F | Hole Location TOL DTP | <input type="checkbox"/> >0,50 [.020] <input type="checkbox"/> 0,50 [.020] <input type="checkbox"/> 0,40 [.016] <input type="checkbox"/> 0,30 [.012] <input type="checkbox"/> 0,25 [.010] <input type="checkbox"/> 0,20 [.008] <input type="checkbox"/> 0,15 [.006] <input type="checkbox"/> 0,10 [.004] <input checked="" type="checkbox"/> <0,10 [.004] <input type="checkbox"/> Other: | |
| G | Internal Layer Clearance (Min) | <input type="checkbox"/> >0,350 [.014] <input type="checkbox"/> 0,350 [.014] <input type="checkbox"/> 0,250 [.010] <input type="checkbox"/> 0,200 [.008] <input type="checkbox"/> 0,150 [.005] <input type="checkbox"/> 0,125 [.005] <input type="checkbox"/> 0,100 [.004] <input type="checkbox"/> 0,075 [.003] <input checked="" type="checkbox"/> <0,075 [.003] | |

| | | | |
|---|--------------------------------------|--|--|
| | | <input type="checkbox"/> Other: | |
| H | Internal Layer Conductor Width (Min) | <input type="checkbox"/> >0,250 [.010] <input type="checkbox"/> 0,250 [.010] <input type="checkbox"/> 0,200 [.008] <input type="checkbox"/> 0,150 [.006] <input type="checkbox"/> 0,125 [.005] <input type="checkbox"/> 0,100 [.004] <input checked="" type="checkbox"/> 0,075 [.003] <input type="checkbox"/> 0,050 [.002] <input type="checkbox"/> <0,050 [.002] <input type="checkbox"/> Other: | |
| J | Internal Layer Process Allowance | <input type="checkbox"/> >0,100 [.004] <input type="checkbox"/> 0,100 [.004] <input type="checkbox"/> 0,075 [.003] <input checked="" type="checkbox"/> 0,050 [.002] <input type="checkbox"/> 0,040 [.0015] <input type="checkbox"/> 0,030 [.0012] <input checked="" type="checkbox"/> 0,025 [.001] <input type="checkbox"/> 0,020 [.0008] <input type="checkbox"/> <0,020 [.0008] <input checked="" type="checkbox"/> Other: Depends on Copper weight | |
| K | External Layer Clearance (Min) | <input type="checkbox"/> >0,350 [.014] <input type="checkbox"/> 0,350 [.014] <input type="checkbox"/> 0,250 [.010] <input type="checkbox"/> 0,200 [.008] <input type="checkbox"/> 0,150 [.006] <input type="checkbox"/> 0,125 [.005] <input type="checkbox"/> 0,100 [.004] <input checked="" type="checkbox"/> 0,075 [.003] <input type="checkbox"/> <0,075 [.003] <input type="checkbox"/> Other: | |

IPC-1710A

| | | | |
|---|--------------------------------------|--|--|
| L | External Layer Conductor Width (Min) | <input type="checkbox"/> >0,250 [.010] <input type="checkbox"/> 0,250 [.010] <input type="checkbox"/> 0,200 [.008] <input type="checkbox"/> 0,150 [.006] <input type="checkbox"/> 0,125 [.005] <input type="checkbox"/> 0,100 [.004] <input checked="" type="checkbox"/> 0,075 [.003] <input type="checkbox"/> 0,050 [.002] <input type="checkbox"/> <0,050 [.002] <input type="checkbox"/> Other: | |
| M | External Layer Process Allowance | <input type="checkbox"/> >0,100 [.004] <input type="checkbox"/> 0,100 [.004] <input type="checkbox"/> 0,075 [.003] <input checked="" type="checkbox"/> 0,050 [.002] <input type="checkbox"/> 0,040 [.0015] <input type="checkbox"/> 0,030 [.0012] <input checked="" type="checkbox"/> 0,025 [.001] <input type="checkbox"/> 0,020 [[.0008] <input type="checkbox"/> <0,020 [.0008] <input checked="" type="checkbox"/> Other: Depends on Copper weight | |
| N | Feature Location DTP | <input type="checkbox"/> >0,50 [.020] <input type="checkbox"/> 0,50 [.020] <input type="checkbox"/> 0,40 [.016] <input type="checkbox"/> 0,30 [.012] <input type="checkbox"/> 0,25 [.010] <input type="checkbox"/> 0,20 [.008] <input type="checkbox"/> 0,15 [.006] <input type="checkbox"/> 0,10 [.004] <input checked="" type="checkbox"/> <0,10 [.004] <input type="checkbox"/> Other: | |

All Dimensions are in millimeters [inches shown in brackets]

SECTION 2.5

QUALITY DEVELOPMENT

DATE COMPLETED
10/27/2016

This section is intended to provide overview information on the quality systems in place in the manufacturing facility.

Site Capability Snapshot (Please Check all that apply.)

| Designators | | | Remarks |
|-------------|----------------------|---|---------|
| A | Strategic Plan | <input checked="" type="checkbox"/> Functional Steering Committee Formed <input checked="" type="checkbox"/> TQM Plan & Philosophy Established & Published <input checked="" type="checkbox"/> Documented Quality Progress Review <input checked="" type="checkbox"/> Implementation & review of Project Team Recommendations <input checked="" type="checkbox"/> TQM Communicated throughout organization <input checked="" type="checkbox"/> Controlled New process Start-up <input checked="" type="checkbox"/> Management Participates in TQM Audits <input checked="" type="checkbox"/> Employee Recognition Program <input checked="" type="checkbox"/> Total TQM Plan/Involvement Customer Training <input type="checkbox"/> Other: | |
| B | Employee Involvement | <input checked="" type="checkbox"/> Certified Training Available <input checked="" type="checkbox"/> Training of Employee Base <input checked="" type="checkbox"/> TQM Team Trained <input type="checkbox"/> Design of Experiment Training and Use <input checked="" type="checkbox"/> New Process Implementation Training <input checked="" type="checkbox"/> Support Personnel Training <input checked="" type="checkbox"/> Statistical Training <input type="checkbox"/> Quality Functional Deployment <input checked="" type="checkbox"/> Ongoing Improvement Program for Employees <input type="checkbox"/> Other: | |
| C | Quality Manual | <input checked="" type="checkbox"/> Quality Manual Completed <input type="checkbox"/> Generic Quality Manual for Facility <input type="checkbox"/> 10% of manufacturing depts. have process specifications <input type="checkbox"/> 25% of manufacturing depts. have process specifications <input type="checkbox"/> 90% of manufacturing depts. have process specifications <input type="checkbox"/> Non-manufacturing Manuals Developed <input type="checkbox"/> 25% of all departments have quality manuals <input type="checkbox"/> 90% of all departments have quality manuals <input checked="" type="checkbox"/> All Manufacturing and support depts. have controlled quality manual <input type="checkbox"/> Other: | |

IPC-1710A

| | | | |
|---|------------------------------|---|--|
| D | Instructions | <input type="checkbox"/> Work Instructions Started <input type="checkbox"/> Quality Instructions Started <input type="checkbox"/> 10% Work Instructions Completed <input type="checkbox"/> 10% Quality Instructions Completed <input type="checkbox"/> 25% Work Instructions Completed, Controlled <input type="checkbox"/> 25% Quality Instructions Completed, Controlled <input type="checkbox"/> 50% Work Instructions Completed, Controlled <input type="checkbox"/> 50% Quality Instructions Completed, Controlled <input checked="" type="checkbox"/> Quality and work Instruct. Completed, Controlled <input type="checkbox"/> Other: | |
| E | SPC Implementation IPC-PC-90 | <input checked="" type="checkbox"/> Plan Exists <input checked="" type="checkbox"/> Training Started <input checked="" type="checkbox"/> Process Data Collected & Analyzed <input type="checkbox"/> All Employees Trained <input type="checkbox"/> First Process Stable & Capable <input checked="" type="checkbox"/> Several Major Processes Stable & Capable <input checked="" type="checkbox"/> Continued Improvement of Stable Processes <input type="checkbox"/> Additional Mfg Processes under Control <input type="checkbox"/> All Processes Under Control <input type="checkbox"/> Other: | |
| F | Supplier Programs/Controls | <input checked="" type="checkbox"/> Supplier Rating Program <input type="checkbox"/> Monthly Analysis Program <input checked="" type="checkbox"/> Key Problems Identified <input checked="" type="checkbox"/> Supplier Reviews Performance Data provided <input type="checkbox"/> TQM Acceptance by suppliers <input type="checkbox"/> 10% of Suppliers Using SPC <input type="checkbox"/> 25% of Suppliers Using SPC <input type="checkbox"/> 50% of Suppliers Using SPC <input checked="" type="checkbox"/> All Key Suppliers using Certified parts program <input type="checkbox"/> Other: | |
| G | Third Party IPC-QS-95 | <input checked="" type="checkbox"/> Instrument Controls in Place <input checked="" type="checkbox"/> Measurement System in Control IPC-PC-90 <input checked="" type="checkbox"/> Document Controls in Place <input type="checkbox"/> Reduced Lot Sampling <input type="checkbox"/> 10% of Processes Under Audit Control <input type="checkbox"/> 50% or Greater of Processes Under Audit Control <input type="checkbox"/> ISO-9003 Certified <input type="checkbox"/> ISO-9002 Certified <input checked="" type="checkbox"/> ISO-9001:2008 | |

Other: AS9100 Rev. B

SECTION 3

EQUIPMENT PROFILE (Pre-Site Audit)

DATE COMPLETED
10/27/2016

* Examples of equipment limitations include:
min/max board size & min/max working area

| 3.1 PHOTOTOOL CAPABILITY | YES | NO | EQUIPMENT | QUANTITY | BOARD SIZE |
|--|-------------------------------------|-------------------------------------|---------------------------------|----------|--------------------------|
| A) AOI of phototool | <input checked="" type="checkbox"/> | <input type="checkbox"/> | Barco/Argos AOI | 3 | 22 x 28, .002 line/space |
| B) AOI CAD reference (CAM) | <input checked="" type="checkbox"/> | <input type="checkbox"/> | U-CAM | 2 | |
| C) Photoplotting | <input checked="" type="checkbox"/> | <input type="checkbox"/> | Gerber Crescent 30 Photoplotter | 2 | 24 x 30 |
| D) Photo reductions | <input type="checkbox"/> | <input checked="" type="checkbox"/> | | | Outsourced |
| E) Film scan and conversion | <input checked="" type="checkbox"/> | <input type="checkbox"/> | | | Outsourced |
| F) Film processing <input type="checkbox"/> air-dried <input checked="" type="checkbox"/> force-dried <input checked="" type="checkbox"/> processed in automatic processor | <input checked="" type="checkbox"/> | <input type="checkbox"/> | Glunz & Jenson 720 | 1 | 24 x 30 |
| G) Media types <input checked="" type="checkbox"/> silver halide film <input type="checkbox"/> glass <input checked="" type="checkbox"/> diazo | <input checked="" type="checkbox"/> | <input type="checkbox"/> | Konica, Folex | N/A | 24 x 30 |

| 3.2 DRILLING EQUIPMENT | YES | NO | EQUIPMENT | QUANTITY | BOARD SIZE |
|-----------------------------|-------------------------------------|-------------------------------------|---------------------|----------|------------|
| A) Manual | <input type="checkbox"/> | <input checked="" type="checkbox"/> | | | |
| B) Optical (single spindle) | <input type="checkbox"/> | <input checked="" type="checkbox"/> | | | |
| C) N.C. drill | <input checked="" type="checkbox"/> | <input type="checkbox"/> | Pluritec & Excellon | 6 | 22 x 28 |

| 3.3 ROUTING EQUIPMENT | YES | NO | EQUIPMENT | QUANTITY | BOARD SIZE |
|-----------------------------|-------------------------------------|-------------------------------------|-------------------------|----------|------------|
| A) Edge beveler | <input checked="" type="checkbox"/> | <input type="checkbox"/> | Bevelmaster Model 035 | 2 | |
| B) Hand router (pin router) | <input type="checkbox"/> | <input checked="" type="checkbox"/> | | | |
| C) N.C. router | <input checked="" type="checkbox"/> | <input type="checkbox"/> | Excellon EX200 & Mark V | 2 | 22 X28 |
| D) N.C. driller/router | <input checked="" type="checkbox"/> | <input type="checkbox"/> | Excellon 200 | 1 | 22 x 28 |
| E) Scoring (profile) | <input checked="" type="checkbox"/> | <input type="checkbox"/> | Accu-Score Jump V-Score | 1 | 22 x 28 |
| F) Scoring (straight line) | <input checked="" type="checkbox"/> | <input type="checkbox"/> | Accu-Score Jump V-Score | 1 | 22 x 28 |

| 3.4 MECHANICAL EQUIPMENT | YES | NO | EQUIPMENT | QTY | EQUIPMENT DIMS |
|--------------------------|-------------------------------------|-------------------------------------|-------------|-----|----------------|
| A) Punch press | <input type="checkbox"/> | <input checked="" type="checkbox"/> | | | |
| B) Shear | <input checked="" type="checkbox"/> | <input type="checkbox"/> | Pexto PH450 | 1 | N/A |
| C) Milling machine | <input checked="" type="checkbox"/> | <input type="checkbox"/> | Excellon | 1 | 22 X 28 |

| 3.5 HOLE PREPARATION (DESMEAR) | YES | NO | EQUIPMENT | QTY | EQUIPMENT DIMS |
|--------------------------------|-------------------------------------|-------------------------------------|------------------------|-----|----------------|
| A) Permagnate | <input checked="" type="checkbox"/> | <input type="checkbox"/> | | | |
| B) Plasma | <input checked="" type="checkbox"/> | <input type="checkbox"/> | Advanced Plasma System | 1 | 22 x 28 |
| C) Mechanical | <input type="checkbox"/> | <input checked="" type="checkbox"/> | | | |
| D) Etchback | <input checked="" type="checkbox"/> | <input type="checkbox"/> | Advanced Plasma System | 1 | 22 x 28 Plasma |

| 3.6 PRIMARY IMAGE APPLICATION | YES | NO | EQUIPMENT | QTY | EQUIPMENT DIMS |
|-------------------------------|-------------------------------------|-------------------------------------|------------------------------|-----|----------------|
| A) Dry film | <input checked="" type="checkbox"/> | <input type="checkbox"/> | Dupont ASL Lam & Western Mag | 3 | 22 x 28 |
| B) Hand screening | <input type="checkbox"/> | <input checked="" type="checkbox"/> | | | |
| C) Machine screening | <input type="checkbox"/> | <input checked="" type="checkbox"/> | | | |
| D) Wet film | <input type="checkbox"/> | <input checked="" type="checkbox"/> | | | |
| E) Liquid photoimageable | <input type="checkbox"/> | <input checked="" type="checkbox"/> | | | |

| 3.7 TYPE OF TREATMENT FOR MULTILAYER INNERLAYERS | YES | NO | EQUIPMENT | QTY | EQUIPMENT DIMS |
|--|-------------------------------------|-------------------------------------|----------------|-----|----------------|
| A) Black oxide | <input type="checkbox"/> | <input checked="" type="checkbox"/> | | | |
| B) Red oxide | <input type="checkbox"/> | <input checked="" type="checkbox"/> | | | |
| C) Copper scrub | <input type="checkbox"/> | <input checked="" type="checkbox"/> | Chemcut 547 xl | 1 | 22x28 |
| D) Durabond | <input type="checkbox"/> | <input checked="" type="checkbox"/> | | | |
| E) Other | <input checked="" type="checkbox"/> | <input type="checkbox"/> | Enthone | 1 | 22 x 28 |

| 3.8 LAMINATION | YES | NO | MATERIAL | QTY | BOARD SIZE (mm) |
|-----------------------|-------------------------------------|-------------------------------------|------------------------------|-----|-----------------|
| A) High pressure | <input checked="" type="checkbox"/> | <input type="checkbox"/> | TMP 30 x 30 & Wabash 30 x 30 | 2 | 22 x 28 |
| B) High temperature | <input checked="" type="checkbox"/> | <input type="checkbox"/> | Same as above | 2 | 22 x 28 |
| C) Vacuum | <input checked="" type="checkbox"/> | <input type="checkbox"/> | Same as above | 2 | 22 x 28 |
| D) Vacuum assist | <input type="checkbox"/> | <input checked="" type="checkbox"/> | | | |
| E) Foil heat assist | <input type="checkbox"/> | <input checked="" type="checkbox"/> | | | |
| F) Separate cool-down | <input checked="" type="checkbox"/> | <input type="checkbox"/> | TMP & Wabash | 2 | 22 x 28 |

| 3.9 ELECTROLESS COPPER PLATING | YES | NO | MATERIAL | QTY | BOARD SIZE (mm) |
|--|-------------------------------------|-------------------------------------|----------|-----|-----------------|
| A) Fully additive application | <input type="checkbox"/> | <input checked="" type="checkbox"/> | | | |
| B) Electroless deposition (semiadditive) | <input checked="" type="checkbox"/> | <input type="checkbox"/> | | 1 | |
| C) Through-hole and via | <input checked="" type="checkbox"/> | <input type="checkbox"/> | | 1 | |

| 3.10 COPPER ELECTROPLATING | YES | NO | MATERIAL | QTY | BOARD SIZE (mm) |
|----------------------------|-------------------------------------|-------------------------------------|--------------------------|-----|-----------------|
| A) Copper sulfate | <input checked="" type="checkbox"/> | <input type="checkbox"/> | | 2 | |
| B) Pyrophosphate | <input type="checkbox"/> | <input checked="" type="checkbox"/> | | | |
| C) Copper fluoborate | <input type="checkbox"/> | <input checked="" type="checkbox"/> | | | |
| D) Other | <input checked="" type="checkbox"/> | <input type="checkbox"/> | BakerReverse Pulse Plate | 1 | 22x28 |

| 3.11 TIN/LEAD SURFACE PLATINGS/COATINGS | YES | NO | MATERIAL | QTY | BOARD SIZE (mm) |
|--|-------------------------------------|-------------------------------------|--|-----|-----------------------|
| A) Tin/lead electroplated | <input type="checkbox"/> | <input checked="" type="checkbox"/> | tanks | 1 | Currently not in use. |
| B) Immersion tin or tin/lead (electroless) | <input checked="" type="checkbox"/> | <input type="checkbox"/> | | 1 | |
| C) Hot air solder leveled (HASL) | <input checked="" type="checkbox"/> | <input type="checkbox"/> | HASL 60/40 Lantronics HASL Lead-Free Lantronics | 2 | |

| 3.12 FUSING PROCESSES | YES | NO | EQUIPMENT | QTY | EQUIPMENT DIMS |
|-------------------------------|-------------------------------------|-------------------------------------|--|-----|---------------------|
| A) I.R. reflow | <input type="checkbox"/> | <input checked="" type="checkbox"/> | | | |
| B) Hot oil reflow | <input type="checkbox"/> | <input checked="" type="checkbox"/> | Tank | | Curently not in use |
| C) Horizontal (hot air level) | <input type="checkbox"/> | <input checked="" type="checkbox"/> | | | |
| D) Vertical (hot air level) | <input checked="" type="checkbox"/> | <input type="checkbox"/> | 63/37 Tin-lead HASL Lantronics & Lead-Free HAL Lantronics | 2 | 22 x 28 |

| 3.13 NICKEL SURFACE PLATING | YES | NO | EQUIPMENT | QTY | EQUIPMENT DIMS |
|-----------------------------|-------------------------------------|--------------------------|----------------------|-----|---|
| A) Electroless nickel | <input checked="" type="checkbox"/> | <input type="checkbox"/> | | 1 | 18 x 24 |
| B) Electroplated nickel | <input checked="" type="checkbox"/> | <input type="checkbox"/> | Tab line & Deep Well | 2 | 6" x 21" Tab line 22 x 28 Deep Well Tank |

| 3.14 GOLD SURFACE PLATING | YES | NO | EQUIPMENT | QTY | EQUIPMENT DIMS |
|---------------------------|-------------------------------------|--------------------------|-----------|-----|----------------|
| A) Immersion gold | <input checked="" type="checkbox"/> | <input type="checkbox"/> | | 1 | 18 x 24 |
| B) Electroplated gold | <input checked="" type="checkbox"/> | <input type="checkbox"/> | | 1 | 22 x 28 |

| 3.15 PALLADIUM SURFACE PLATING | YES | NO | EQUIPMENT | QTY | EQUIPMENT DIMS |
|--------------------------------------|-------------------------------------|-------------------------------------|-----------|-----|----------------|
| A) Electroless palladium (immersion) | <input type="checkbox"/> | <input checked="" type="checkbox"/> | | | |
| B) Electroplated palladium | <input checked="" type="checkbox"/> | <input type="checkbox"/> | | 1 | 22 x 28 |

| 3.16 SOLDERMASK | YES | NO | EQUIPMENT | QTY | EQUIPMENT DIMS |
|--------------------------------|-------------------------------------|--------------------------|---|-----|----------------|
| A) Screened deposited image | <input checked="" type="checkbox"/> | <input type="checkbox"/> | Barnaby stations | 2 | 18 x 24 |
| B) Dry film photoimageable | <input checked="" type="checkbox"/> | <input type="checkbox"/> | DuPont & Dynachem | 1 | 18 x 24 |
| C) Liquid photoimageable | <input checked="" type="checkbox"/> | <input type="checkbox"/> | Circuit Automation DP1500 TC 120 Tunnel oven | 1 | 22 x 28 |
| D) Dry film/liquid combination | <input checked="" type="checkbox"/> | <input type="checkbox"/> | Same equipment as above | 2 | 22 x 28 |

| 3.17 ORGANIC SURFACE PROTECTION | YES | NO | EQUIPMENT | QTY | EQUIPMENT DIMS |
|---------------------------------|-------------------------------------|-------------------------------------|-------------|-----|----------------|
| A) Benzotriazole | <input type="checkbox"/> | <input checked="" type="checkbox"/> | | | |
| B) Imidazole | <input checked="" type="checkbox"/> | <input type="checkbox"/> | Entek 106HT | 1 | 22 x 28 |
| C) Benzimidazole | <input type="checkbox"/> | <input checked="" type="checkbox"/> | | | |

| 3.18 MICROSECTION CAPABILITY | YES | NO | EQUIPMENT | QUANTITY | EQUIPMENT TYPE |
|-------------------------------|-------------------------------------|--------------------------|--------------------------|----------|----------------|
| A) Manual | <input checked="" type="checkbox"/> | <input type="checkbox"/> | Struers Rotopol, Buehler | 1 | |
| B) Single cavity automated | <input checked="" type="checkbox"/> | <input type="checkbox"/> | Struers Rotopol | 1 | |
| C) Multiple cavity automated | <input checked="" type="checkbox"/> | <input type="checkbox"/> | Struers Rotopol | 1 | |
| D) Plating thickness analysis | <input checked="" type="checkbox"/> | <input type="checkbox"/> | Pax-It2 | 1 | |

| 3.19 CHEMICAL ANALYSIS | YES | NO | EQUIPMENT | QUANTITY | EQUIPMENT TYPE |
|----------------------------|-------------------------------------|--------------------------|--------------------------|----------|---------------------------------|
| A) Etching chemistry | <input checked="" type="checkbox"/> | <input type="checkbox"/> | LAB & XRF | 1 | |
| B) Plating chemistry | <input checked="" type="checkbox"/> | <input type="checkbox"/> | LAB | 1 | *Use outside Lab for comparison |
| C) Effluent (PPM) analysis | <input checked="" type="checkbox"/> | <input type="checkbox"/> | Hanna 9812 Pri Perimeter | 1 | |

| 3.20 ELECTRICAL TEST EQUIPMENT | YES | NO | EQUIPMENT | QUANTITY | EQUIPMENT TYPE |
|--------------------------------|-------------------------------------|-------------------------------------|---|----------|--|
| A) Continuity and shorts | <input checked="" type="checkbox"/> | <input type="checkbox"/> | Circuit Liner 2S | 1 | Top side Fixture 16x 20 Bottom side Fixture 18 x 24 |
| B) Fixture development | <input checked="" type="checkbox"/> | <input type="checkbox"/> | Lavenir & Genesis | 2 | |
| C) Flying Probe tester | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | Mania loc8 Flying Probe & Mania Ultim8 Flying Probe | 2 | Removed 3 NewSystems Flying Grid testers. Not in use, Mania, closed down NewSystems after acquiring them. |
| D) Impedance control | <input checked="" type="checkbox"/> | <input type="checkbox"/> | Polar Instruments CITS 500s & Impedance Model Calculator | 1 | Complete TDR System |

MASTER EQUIPMENT LISTING

FORM MQP 10

| |
|------------------------------|
| DATE COMPLETED 10/27/2016 |
|------------------------------|

Please complete a Master Equipment List. You may use your own form or the MQP Form 10.

| IDENTIFICATION | EQUIPMENT NAME/DESCRIPTION | MFR. TYPE/MODEL | EQUIP. LIMITS | ACCURACY | CALIBRATION FREQUENCY | REMARKS |
|----------------|-------------------------------|-----------------|---------------|----------|-----------------------|---------|
| | See Facility & Equipment List | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |

SECTION 4

TECHNOLOGY PROFILE SPECIFICS

| |
|------------------------------|
| DATE COMPLETED 10/27/2016 |
|------------------------------|

4.1 ADMINISTRATION


| 4.1.1 CAPACITY PROFILE | | |
|--|--------|----------------------|
| A) Total annual capacity in square meters (surface area) per month | varies | Varies on technology |
| B) Presently running at ____ % of capacity | 60% | 1 ½ Shifts |


| 4.1.2 PERCENTAGE OF DOLLAR VOLUME | | |
|-------------------------------------|----|---|
| A) Single sided (rigid) | 5 | Percentages do not represent a dollar amount, based on percentage of product mix. |
| B) Double sided (rigid) | 15 | |
| C) Multilayer (rigid) | 63 | |
| D) Single side (unreinforced-flex) | 2 | |
| E) Double sided (unreinforced-flex) | 5 | |
| F) Multilayer (unreinforced-flex) | 5 | |
| G) Multilayer (rigid/flex) | 5 | |

| 4.1.3 PANEL PRODUCTION PROFILE | | |
|---------------------------------------|---|--|
| A) Size of a production lot in panels | | |
| 1) Normal | 20 panels per lot run X multiple lots for larger quantity orders. | |
| 2) Smallest | 1 panel for prototypes | |
| B) Number of panels per month | | |
| 1) High Production | Offshore on approved orders by customer only. | |
| 2) Medium Production | 15% | |
| 3) Low Production | 20 % | |
| 3) Short run | 30 % | |
| 4) Prototype | 35% | |

| | | | |
|--|-------------------------------------|-------------------------------------|---|
| C) Average lead time (delivery) as defined in B) | | | |
| 1) High Production | | | 3-5 weeks |
| 2) Medium Production | | | 1-4 Weeks |
| 3) Low Production | | | 2 days - 2 Weeks |
| 3) Short run | | | 24 hr – 10 Days |
| 4) Prototype | | | 24 hrs –10 Days |
| Quick turn - No. of days_____. | | | |
| D) Product delivered in full panel or array sub-panel format | | | |
| 1) Total in panel or array format | | | 25 % |
| 2) Scored format | | | 30 % |
| 3) Tab breakaway format | | | 15 % |
| 4) Other | | | |
| 5) Total to customer layout | | | |
| 6) Total to manufacturing layout | | | |
| E) Product delivered in board format | | | |
| 1) Total in board format | | | 30 % |
| 2) Extracted: scored to size | | | 0 |
| 3) Extracted: sheared to size | | | 0 |
| 4) Extracted: routed to size | | | 30 % |
| 4.1.4 APPROVAL AND CERTIFICATION | YES | NO | COMMENTS |
| A) Company approvals | | | |
| 1) UL approval | <input checked="" type="checkbox"/> | <input type="checkbox"/> | 94V Level __0 |
| 2) Canadian standards | <input type="checkbox"/> | <input checked="" type="checkbox"/> | |
| 3) MIL-P-55110 | <input checked="" type="checkbox"/> | <input type="checkbox"/> | FR and Polyimide with certified etchback. |
| 4) MIL-P-50884 | <input type="checkbox"/> | <input checked="" type="checkbox"/> | |
| 5) AS9100 | <input checked="" type="checkbox"/> | <input type="checkbox"/> | Aerospace certified |

| | | | |
|---|-------------------------------------|-------------------------------------|------------------------------------|
| 6) ISO-9001:2008 | <input checked="" type="checkbox"/> | <input type="checkbox"/> | ISO 9001:2008 |
| 7) ISO-14000 | <input type="checkbox"/> | <input checked="" type="checkbox"/> | |
| 8) BABT | <input type="checkbox"/> | <input checked="" type="checkbox"/> | |
| 9) EEC | <input type="checkbox"/> | <input checked="" type="checkbox"/> | |
| 10) Customer satisfaction | <input checked="" type="checkbox"/> | <input type="checkbox"/> | Customer's internal specifications |
| B) Other certification information | | | |
| 1)Laminate | <input checked="" type="checkbox"/> | <input type="checkbox"/> | |
| 2)Quality standards | <input checked="" type="checkbox"/> | <input type="checkbox"/> | |
| 3)Equipment calibration | <input checked="" type="checkbox"/> | <input type="checkbox"/> | 70% Third Party 30% In House |

| 4.1.5 CUSTOMER INTERFACE PROFILE | YES | NO |  |
|---|-------------------------------------|--------------------------|--|
| A) Modem capability | <input checked="" type="checkbox"/> | <input type="checkbox"/> | Replaced with E-mail And FTP site |
| B) Baud rate | | | |
| C) Data verification technique | <input checked="" type="checkbox"/> | <input type="checkbox"/> | Net-list verification |
| D) Engineering change order process | <input checked="" type="checkbox"/> | <input type="checkbox"/> | Bacon System |
| E) Job status reporting to customers | <input checked="" type="checkbox"/> | <input type="checkbox"/> | Bacon JTS Job Tracking Systems (Barcode) |

| 4.1.6 OTHER CAPABILITIES | YES | NO |  |
|--|-------------------------------------|--------------------------|--|
| A) Facility research and development | <input checked="" type="checkbox"/> | <input type="checkbox"/> | |
| B) (Automated) On-line shop floor control/MRP system | <input checked="" type="checkbox"/> | <input type="checkbox"/> | Bacon Systems JTS |
| C) Process control system | <input checked="" type="checkbox"/> | <input type="checkbox"/> | ISO |
| D) Operator training system | <input checked="" type="checkbox"/> | <input type="checkbox"/> | IPC and Mil |

4.2 PROCESS ORIENTATION

| 4.2.1 LAMINATE MATERIAL | | |
|--|-----|--|
| A) Most commonly used laminates (G10, FR4, etc.) | | Brand name ARLON Type Polyimide and FR4 Brand name ISOLA Type Polyimide and FR4 Brand name NELCO Type Polyimide and FR4 Brand name Rogers Type RF Brand name Taconic Type RF |
| B) Other laminate material | | |
| 1) Planar resistor layers | | UL approved <input type="checkbox"/> |
| 2) FR4 Epoxy | YES | UL approved <input checked="" type="checkbox"/> |
| 3) Kevlar | | UL approved <input type="checkbox"/> |
| 4) Teflon | YES | UL approved <input type="checkbox"/> |
| 5) Polyimide | YES | UL approved <input checked="" type="checkbox"/> |
| 6) Cyanate ester | YES | UL approved <input type="checkbox"/> |
| 7) Other FLEX | YES | UL approved <input type="checkbox"/> |
| C) Specification to which laminate is purchased (check all that apply) <input type="checkbox"/> MIL-P-13949 <input checked="" type="checkbox"/> IPC-4204 <input checked="" type="checkbox"/> IPC-4101 <input checked="" type="checkbox"/> UL Approved <input checked="" type="checkbox"/> IPC-4103 <input type="checkbox"/> Other <input checked="" type="checkbox"/> IPC-4202 <input checked="" type="checkbox"/> IPC-4203 | | MIL-P-13949 is obsolete |
| D) Laminate storage <input type="checkbox"/> Uncontrolled <input checked="" type="checkbox"/> Humidity controlled <input checked="" type="checkbox"/> Temperature controlled <input type="checkbox"/> Dry box <input checked="" type="checkbox"/> JIT inventory | | |
| E) Panel size configurations in X, Y dimensions maximum X <u>558.8</u> Y <u>711.2</u> mm minimum X <u>304.8</u> Y <u>457.2</u> mm other X _____ Y _____mm | | |

| 4.2.2 PROCESS PRECISION SPECIFICS | YES | NO | SYSTEM | COMMENT |
|--|-------------------------------------|-------------------------------------|--------|---|
| A) Maximum printed board thickness built in volume | | | | |
| 1) Single sided | | | .062 | |
| 2) Double sided | | | .125 | |
| 3) Multilayer | | | .250 | |
| 4) Rigid flex | | | .062 | |
| B) Printed board electrical performance capability | | | | |
| 1) Impedance control | <input checked="" type="checkbox"/> | <input type="checkbox"/> | | Polar Instruments TDR System |
| 2) Capacitance control | <input checked="" type="checkbox"/> | <input type="checkbox"/> | | Mania Technology ULTIM8 Flying Probe LCR meter |
| 3) Microstrip boards | <input checked="" type="checkbox"/> | <input type="checkbox"/> | | |
| C) Tooling system description | | | | |
| 1) Same holes in panels used for all processes | <input type="checkbox"/> | <input checked="" type="checkbox"/> | | |
| 2) Optical registration | <input checked="" type="checkbox"/> | <input type="checkbox"/> | | Process: C. A. Pucard tooling w/ Optical system |
| 3) Other | <input checked="" type="checkbox"/> | <input type="checkbox"/> | | Multi Line Punch Sys. |

| 4.2.3 OTHER PROCESS ORIENTATION SPECIFICS | YES | NO | SYSTEM | COMMENT |
|---|-------------------------------------|-------------------------------------|--------------------------------------|---------|
| A) Solder mask over bare copper | <input checked="" type="checkbox"/> | <input type="checkbox"/> | | |
| B) Plating/coating information | | | | |
| 1) Tin/lead reflow | <input type="checkbox"/> | <input checked="" type="checkbox"/> | Not in use: Storage | |
| 2) Hot air leveling | <input checked="" type="checkbox"/> | <input type="checkbox"/> | 63/37 HASL Tin-Lead Lead-Free HAL | |
| 3) Azole organic | <input checked="" type="checkbox"/> | <input type="checkbox"/> | | |
| 4) Conductive | <input checked="" type="checkbox"/> | <input type="checkbox"/> | | |
| C) Hole formation | | | | |
| 1) Hole cleaning | <input checked="" type="checkbox"/> | <input type="checkbox"/> | APS/March Plasma System | |
| 2) Hole cleanliness verified | <input checked="" type="checkbox"/> | <input type="checkbox"/> | X-section | |

4.3 PRODUCT DESCRIPTION

*CONSISTENCY IMPLIES YIELDS IN EXCESS OF 80%

| 4.3.1. THROUGH HOLE INSERTION | Size (mm) | Tol. | Comments |
|--|---------------------|--------------------------|---------------------|
| A) Smallest conductor width and tolerance produced with consistency | | | |
| 1) Outer layers (print and etch) | Size <u>076</u> mm | Tol \pm <u>010</u> .mm | |
| 2) Inner layers (print and etch) | Size <u>076</u> mm | Tol \pm <u>010</u> .mm | |
| 3) Outer layers (plated) | Size <u>089</u> mm | Tol \pm <u>010</u> .mm | |
| 4) Inner layers (plated) | Size <u>089</u> mm | Tol \pm <u>010</u> .mm | |
| 5) Outer layers (additive plating) | Size <u>076</u> mm | Tol \pm <u>010</u> .mm | |
| 6) Inner layers (additive plating) | Size <u>076</u> mm | Tol \pm <u>010</u> .mm | |
| B) Smallest plated-through hole (PTH) and tolerance consistently produced in 1.5mm thickness material or multilayer board | | | |
| 1) Minimum PTH diameter | Size <u>152</u> mm | Tol \pm <u>076</u> .mm | |
| 2) Largest panel where this hole can be controlled (across diagonal) | Size <u>457</u> mm | Tol \pm <u>076</u> .mm | |
| C) Largest hole size that can be drilled and plated through in a 1.25mm diameter land while maintaining an annular ring of 0.125mm in large/small boards | .9525 mm | | |
| 1) Largest board size (across diagonal) | Size <u>609</u> mm | | |
| 2) Largest hole diameter | Size mm | | Per Print unlimited |
| 3) Smallest board size (across diagonal) | Size <u>7.62</u> mm | | |
| 4) Largest hole diameter | Size ____ mm | | Per Print unlimited |
| D) Surface mount land pattern pitch (check all that apply) | | | |
| <input checked="" type="checkbox"/> 1.27mm [.050] <input checked="" type="checkbox"/> 0.63mm [.025] | | | |
| <input checked="" type="checkbox"/> 0.5mm [.020] <input checked="" type="checkbox"/> 0.4mm [.016] | | | |
| <input checked="" type="checkbox"/> 0.3mm [.012] <input checked="" type="checkbox"/> 0.25mm [.010] | | | |
| <input type="checkbox"/> Other ____ . | | | |

| | | | |
|---|--|--|--|
| E) Solder mask dam between lands (check all that apply) <input checked="" type="checkbox"/> 1.27mm [.050] <input checked="" type="checkbox"/> 0.63mm [.025] <input checked="" type="checkbox"/> 0.5mm [.020] <input checked="" type="checkbox"/> 0.4mm [.016] <input checked="" type="checkbox"/> 0.3mm [.012] <input checked="" type="checkbox"/> 0.25mm [.010] <input checked="" type="checkbox"/> Other <u>.101mm</u> (.004) | | | |
| F) Flatness tolerance (bow & twist) after reflow or solder coating <input type="checkbox"/> 1.5% <input checked="" type="checkbox"/> 1.0% <input type="checkbox"/> 0.5% <input type="checkbox"/> Other ____ | | | |

| 4.3.2 PRODUCT QUALITATIVE AND QUANTITATIVE INFORMATION | YES | NO | QUANTITY OF PARTS | NUMBER OF FABRICATIONS | COMMENTS |
|---|-------------------------------------|--------------------------|-------------------|------------------------|----------|
| A) Multilayer layer count | | | | | |
| 1) Maximum layers fabricated in volume (Maximum Lot) | YES | | | 440 | |
| 2) Maximum layers fabricated in prototype (Minimum Lot) | YES | | | 200 | |
| B) Buried vias produced consistently in volume | YES | <input type="checkbox"/> | | | |
| 1) Size | | | | .010" | |
| 2) Number of layers | | | | 24 | |
| B) Blind vias produced consistently in volume | YES | <input type="checkbox"/> | | | |
| 1) Size | | | | .01 | |
| 2) Number of layers | | | | 24 | |
| 1) Controlled depth drilling | <input checked="" type="checkbox"/> | <input type="checkbox"/> | | | |
| 2) Total number of layers | | | | | |

4.4. TESTING CAPABILITY

| 4.4.1 TEST AND TEST EQUIPMENT CAPABILITY | YES | NO | COMMENTS |
|--|-------------------------------------|--------------------------|---|
| A) SMT centerline pitch that can be electrically tested <input checked="" type="checkbox"/> 0.63mm [.025] <input checked="" type="checkbox"/> 0.5mm [.020] <input checked="" type="checkbox"/> 0.4mm [.016] <input checked="" type="checkbox"/> 0.3mm [.012] <input checked="" type="checkbox"/> 0.25mm [.010] <input checked="" type="checkbox"/> 0.2mm (.008) | | | |
| B) Double sided simultaneous electrical testing | <input checked="" type="checkbox"/> | <input type="checkbox"/> | 2 DIFFERENT TEST TYPE TESTERS: Fixture, & Flying Probe. |
| 1) Equipment type | <input checked="" type="checkbox"/> | <input type="checkbox"/> | 2 DIFFERENT TEST TYPE TESTERS: Fixture, & Flying Probe. |
| 2) X-ray fluorescence inspection equipment | <input checked="" type="checkbox"/> | <input type="checkbox"/> | CMI 900 |
| 3) TDR equipment | <input checked="" type="checkbox"/> | <input type="checkbox"/> | Polar Instruments system |
| 4) Hi-pot test equipment | <input checked="" type="checkbox"/> | <input type="checkbox"/> | Mania Technologies Flying Probe tester |

IPC-1710A

| | | | |
|----------------------------|-------------------------------------|-------------------------------------|---|
| 5) Four-wire kelvin tester | <input type="checkbox"/> | <input checked="" type="checkbox"/> | |
| 6) Capacitance meter | <input checked="" type="checkbox"/> | <input type="checkbox"/> | Simpson Model # 401 |
| 7) Cleanliness testing | <input checked="" type="checkbox"/> | <input type="checkbox"/> | Omega Meter Model 600 SMD Ionics Contamination systems with heater. |

| 4.4.2 AUTOMATED OPTICAL INSPECTION USAGE | PERCENTAGE | COMMENTS |
|---|------------|------------|
| A) Before etching | 25% | Fine Lines |
| B) After etching | 100% | |
| C) Internal layers | 100% | |
| D) Final inspection | 0 | |
| E) Other | 75% | Film |
| F) Conductor/clearance normally inspected by AOI equipment | | |
| 1) <input checked="" type="checkbox"/> 0.05mm [.002] | | |
| 2) <input checked="" type="checkbox"/> 0.05-.10mm [.002-.004] | | |
| 3) <input type="checkbox"/> >.10mm [.004] | | |
| 4) <input checked="" type="checkbox"/> Planes | | |
| G) CAD download to AOI | Yes | |

SECTION 5

QUALITY PROFILE

| |
|------------------------------|
| DATE COMPLETED 10/27/2016 |
|------------------------------|

GENERAL INFORMATION

| | |
|--|----------------------------|
| COMPANY NAME Multilayer Technology | |
| CONTACT Alan Cochrane / Ashok Patel | |
| TELEPHONE NUMBER 972-790-0062 | FAX NUMBER 972-790-0293 |

This section of the Manufacturer’s Qualification Profile is intended to describe the Total Quality Management (TQM) activity in place of being implemented at the manufacturing facility identified in the site description of this MQP.

To ease in the task of identifying the TQM program being planned or underway at the manufacturing site, the activities have been divided into twenty sections which when completed, provide the total picture of the posture toward managing quality issues. Each section contains a number of questions with regard to the topic under review.

It is not the intent to have the questions be all encompassing, nor is every question applicable to all manufacturers. However, identification of the status, related to each questions, when considered as a whole will convey an impression of the progress that the company has achieved in adopting the principles of total quality management.

The twenty sections, in order of the occurrence are:

- | | |
|---------------------------------------|--|
| 5.1 General Quality Programs | 5.11 Statistical Process Control |
| 5.2 New Products/Technical Services | 5.12 Problem Solving |
| 5.3 Customer Satisfaction | 5.13 In-Process Control |
| 5.4 Computer Integrated Manufacturing | 5.14 Receiving Inspection |
| 5.5 Process Documentation | 5.15 Material Handling |
| 5.6 Quality Records | 5.16 Non-Conforming Material Control |
| 5.7 Skill, Training & Certification | 5.17 Inspection and Test Plan |
| 5.8 Subcontractor Control | 5.18 Product Inspection/Final Audit |
| 5.9 Calibration Control | 5.19 Tooling Inspection, Handling, & Storage |
| 5.10 Internal Audits | 5.20 Corrective Action |

Each section provides a status report related to each question. The question may not be applicable, no activity has started as yet, or the company may have developed an approach to the issues raised by the questions. An (X) is indicated in the appropriate column. If deployment/implementation has started, the status is reported as percent deployment; this is indicated in column 4. The percentage number closely approximates the status of deployment. If deployment exists, the percentage results that have been achieved is indicated in column 5. Results are based on expected goals. Not providing percent information in either the deployment or results column implies a lack of activity in the particular area.

The quality descriptions requested are completed on the following pages by checking (X) the appropriate column to reflect the status of the manufacturing facility TQM program. Additional information may be provided as comments shown below, or on individual sections, or additional sheets as necessary.

| COMMENTS |
|----------|
| |
| |
| |
| |
| |
| |

| 5.1 GENERAL QUALITY PROGRAMS | | STATUS | | | | |
|------------------------------|--|----------------|-------------|--------------------|------------------|-----------------|
| | | Not Applicable | Not Started | Approach Developed | Percent Deployed | Percent Results |
| DESCRIPTION OF PROGRAM | | | | | | |
| 1. | Are quality objectives and responsibilities clearly stated, widely distributed and understood through the company? | | | Y | 100 | 100 |
| 2. | Is there a quality function or well defined organization which provides customer advocate guidance to the total organization and is this position fully supported by management? | | | Y | 100 | 100 |
| 3. | Does a quality measurement system exist with clearly defined metrics and is it utilized as a management tool? | | | Y | 100 | 100 |
| 4. | Are work instructions approved and controlled; and are they under revision control? | | | Y | 100 | 100 |
| 5. | Are the quality procedures and policies current and available at the point of application; and are they under revision control? | | | Y | 100 | 100 |
| 6. | Are benchmark and customer satisfaction studies done to determine best in class for all products, services, and administrative functions; and are quality goals set? | | | Y | 100 | 100 |
| 7. | Are Statistical Process Control (SPC) principles understood by all levels of management? | | | Y | 50 | 50 |
| 8. | Are there programs with sufficient resources assigned to support corrective actions and prevention? | | | Y | 100 | 100 |
| 9. | Does management solicit and accept feedback from the work force? | | | Y | 100 | 100 |
| 10. | Is there management support of ongoing training (including quality training), and is it documented by an organizational training plan? | | | Y | 100 | 100 |
| 11. | Are there regular management reviews of elements of the quality improvement process, including feedback for corrective action, and are the results acted upon? | | | Y | 100 | 100 |
| 12. | Are the quality and reliability goals aggressive relative to customer expectations and targeted at continuous improvement? | | | Y | 100 | 100 |
| 13. | Are the people who are responsible for administering the quality assurance function technically informed? | | | Y | 100 | 100 |
| 14. | Does Management have a "defect prevention" attitude to achieve continuous improvement? | | | Y | 100 | 100 |

| 5.2 NEW PRODUCTS/TECHNICAL SERVICES | | STATUS | | | | |
|-------------------------------------|---|----------------|-------------|--------------------|------------------|-----------------|
| | | Not Applicable | Not Started | Approach Developed | Percent Deployed | Percent Results |
| DESCRIPTION OF PROGRAM | | | | | | |
| 1. | Do new product/technology/service development policies and procedures exist, and do they result in clearly defined project plans with appropriate measureables and approvals? | | | Y | 90 | 90 |
| 2. | Is quantitative benchmarking used to evaluate all new products/technologies/services in comparison to best-in-class offerings? | | | Y | 100 | 100 |
| 3. | Does a roadmap exist to ensure continued development of leading edge, best-in-class products/technology/services? | | | Y | 95 | 95 |
| 4. | Is the capability of each operation which controls critical-to-function characteristics for new products, fully certified? | | | Y | 100 | 100 |
| 5. | Are statistical tools used in the development of robust (high yield) new processes, products, and services? | | | Y | 100 | 100 |
| 6. | When new product/technology/service requires a new process, is it developed jointly and concurrently with the customer and/or suppliers? | | | Y | 100 | 100 |
| 7. | Are design reviews conducted on a scheduled basis which properly address the process capability indices of critical-to-function and product/service characteristics? | | | Y | 100 | 100 |
| 8. | Is the new product/technology/service, as produced by the process, verified to meet all customer satisfaction requirements? | | | Y | 100 | 100 |

| | | | | | | |
|--|--|--|--|--|--|--|
| | | | | | | |
| | | | | | | |

| 5.3 CUSTOMER SATISFACTION | | STATUS | | | | |
|---------------------------|--|----------------|-------------|--------------------|------------------|-----------------|
| | | Not Applicable | Not Started | Approach Developed | Percent Deployed | Percent Results |
| DESCRIPTION OF PROGRAM | | | | | | |
| 1. | Is there a measurement system in place to assess the customer's perception of complete performance? | | | Y | 100 | 100 |
| 2. | Is an independent (unbiased) customer survey routinely conducted? | | | Y | 100 | 100 |
| 3. | Is there an internal measurement system within the organization which correlates to the level of customer satisfaction? | | | Y | 100 | 100 |
| 4. | Are there specific goals for achieving Total Customer Satisfaction, both internal and external? | | | Y | 100 | 100 |
| 5. | To what extent are customer satisfaction goals disseminated and understood by everyone in the organization? | | | Y | 100 | 100 |
| 6. | Does management regularly review and assess all operating systems to determine if barriers to customer satisfaction exist and are appropriate action plans then implemented? | | | Y | 100 | 100 |
| 7. | Is there a method in place to obtain future customer requirements? | | | Y | 100 | 100 |
| 8. | Are all findings of customer dissatisfaction reported back to the proper organization for analysis and corrective action? | | | Y | 100 | 100 |
| 9. | Are customer satisfaction requirements formally defined and documented, and are they based on customer input? | | | Y | 100 | 85 |
| 10. | Do all support organizations understand their role in achieving total customer satisfaction? | | | Y | 100 | 100 |

| 5.4 COMPUTER INTEGRATED MANUFACTURING | | STATUS | | | | |
|---------------------------------------|---|----------------|-------------|--------------------|------------------|-----------------|
| | | Not Applicable | Not Started | Approach Developed | Percent Deployed | Percent Results |
| DESCRIPTION OF PROGRAM | | | | | | |
| 1. | Are systems integrated to allow electronic transfer of information between multiple systems to eliminate redundant data entry? | | | Y | 100 | 100 |
| 2. | Can customers electronically transfer CAD/CAM directly into manufacturing? | N/A | | | | |
| 3. | Can customers electronically transfer order information directly into the business systems? | N/A | | | | |
| 4. | Is data electronically shared between shop floor control and process control systems (i.e., CNC, SPC, Electrical Test, AOI, etc.)? | | | Y | 100 | 100 |
| 5. | Are planning systems (MRP, forecasting, capacity planning, financial planning, etc.) electronically integrated with operation systems (order processing, purchasing, inventory management, shop floor control, financial/cost control, etc.)? | | | Y | 100 | 100 |
| 6. | Is information available from system processes in real time (vs. batch processing)? | | | Y | 100 | 100 |
| 7. | Are processes and procedures documented and available on-line? | | | Y | 100 | 100 |
| 8. | Do all functional departments have system access to key financial, manufacturing, sales, and operational data, as it relates to their functional objectives? | | | Y | 100 | 100 |
| 9. | Are computer simulation and design tools used to the maximum extent practicable in the design of new products/technologies/services | | | Y | 100 | 100 |

COMMENTS:

3. All electronic data is controlled and managed through Cad Engineering.

4. All customer electronic transfer information such as PO, WIP, Change Orders, etc are controlled and managed through Inside Sales Support. We have procedures for changes and authorization that has to be managed through our system for control measures.

7.0 Currently upgrading to on-line.

| 5.5 PROCESS DOCUMENTATION | | STATUS | | | | |
|---------------------------|--|----------------|-------------|--------------------|------------------|-----------------|
| | | Not Applicable | Not Started | Approach Developed | Percent Deployed | Percent Results |
| DESCRIPTION OF PROGRAM | | | | | | |
| 1. | Are manufacturing product, process, and configuration documents under issue control? | | | Y | 100 | 100 |
| 2. | Are "preliminary" and "special product" specifications controlled? | | | Y | 100 | 100 |
| 3. | Does the system ensure that the most current customer specifications are available to the manufacturing personnel? | | | Y | 100 | 100 |
| 4. | Does the system ensure that the most current material specifications are available to the procurement function? | | | Y | 100 | 100 |
| 5. | Are incoming orders reviewed for revisions and issue changes? | | | Y | 100 | 100 |
| 6. | Is conformance to customer specifications assured before an order is accepted? | | | Y | 100 | 100 |
| 7. | Is customer feedback provided when designs do not meet manufacturability requirements? | | | Y | 100 | 100 |
| 8. | Are critical characteristics classified, relative to impact on product performance? | | | Y | 100 | 100 |
| 9. | Are customers informed of changes made to products controlled by customer drawings or specifications? | | | Y | 100 | 100 |
| 10. | Is there an effective internal deviation control procedure and, are customer requested deviations documented and followed? | | | Y | 100 | 100 |
| 11. | Do new product development procedures exist, and are they followed in the design development process? | | X | | | |

| 5.6 QUALITY RECORDS | | STATUS | | | | |
|------------------------|--|----------------|-------------|--------------------|------------------|-----------------|
| | | Not Applicable | Not Started | Approach Developed | Percent Deployed | Percent Results |
| DESCRIPTION OF PROGRAM | | | | | | |
| 1. | Are records of inspection and process control maintained and available for review? | | | Y | 100 | 100 |
| 2. | Are records of equipment and equipment maintenance kept? | | | Y | 100 | 100 |
| 3. | Is the record and sample retention program defined? | | | Y | 100 | 100 |
| 4. | Are quality data used as a basis for corrective action? | | | Y | 100 | 100 |
| 5. | Are quality data used in reporting performance and trends to management? | | | Y | 100 | 100 |
| 6. | Are quality data used in supporting certifications of quality furnished to customers? | | | Y | 100 | 100 |
| 7. | Is field information used for corrective action? | | | Y | 100 | 100 |
| 8. | Does a cost of quality measurement system exist? | | | Y | 100 | 100 |
| 9. | Are customer reported quality problems responded to, and resolved in the time period requested? | | | Y | 100 | 100 |
| 10. | Is quality information on production material rejects provided to sub-suppliers with required corrective action? | | | Y | 100 | 100 |
| 11. | Are computers used to collect and analyze quality data? | | | Y | 80 | 80 |

COMMENTS

11. Customer provide design, we are design exempt. ISO Exclusion.

| 5.7 SKILLS, TRAINING, & CERTIFICATION | | STATUS | | | | |
|--|---|----------------|-------------|--------------------|------------------|-----------------|
| DESCRIPTION OF PROGRAM | | Not Applicable | Not Started | Approach Developed | Percent Deployed | Percent Results |
| 1. | Does management ensure that all personnel are trained in their role for achieving Total Customer Satisfaction? | | | Y | 100 | 100 |
| 2. | Do all personnel understand how their performance impacts internal and external customer satisfaction? | | | Y | 100 | 100 |
| 3. | Do all personnel who contact external customers reflect quality improvement programs? | | | Y | 100 | 100 |
| 4. | Do personnel participate in professional societies and growth programs? | | | Y | 30 | 30 |
| 5. | Are all personnel trained in sufficient detail to support key initiatives? | | | Y | 100 | 100 |
| 6. | Are the results of training evaluated and indicated program changes made? | | | Y | 100 | 100 |
| 7. | Does a policy exist which encourages the cross training and rotation of personnel, and is this policy used as the basis of job progression? | | | Y | 100 | 100 |
| 8. | Are performance standards participatively developed, and regularly applied for all personnel? | | | Y | 50 | 50 |
| 9. | Are Total Customer Satisfaction programs and resulting successes publicized to all personnel? | | | Y | 100 | 100 |
| 10. | Do goal setting and reward/incentive programs support the quality improvement process? | | | Y | 50 | 50 |

| 5.8 SUBCONTRACTOR CONTROL | | STATUS | | | | |
|----------------------------------|--|----------------|-------------|--------------------|------------------|-----------------|
| DESCRIPTION OF PROGRAM | | Not Applicable | Not Started | Approach Developed | Percent Deployed | Percent Results |
| 1. | Are requirements defined, communicated, and updated to ensure that the supplier understands expectations? | | | Y | 100 | 100 |
| 2. | Does a system exist which measures the performance of the supplier and communicates such information to the supplier? (i.e., supplier rating system) | | | Y | 100 | 100 |
| 3. | Have the organization's processes been characterized to identify the critical requirements for the suppliers products? | | | Y | 100 | 100 |
| 4. | Have the capabilities of the supplier's processes been assessed and considered in the establishment of the requirements? | | | Y | 100 | 100 |
| 5. | Have partnerships been established with suppliers, and is assistance provided to ensure that each supplier has the capability to consistently supply conforming products? | | | Y | 100 | 100 |
| 6. | Have quality and cycle time metrics and improvement goals been established participatively with the supplier? | | | Y | 100 | 100 |
| 7. | Has a system been established with the supplier for identification and verification of corrective action? | | | Y | 100 | 100 |
| 8. | Have the requirements for supplier materials been properly characterized and specified to ensure conformance of the product/service to the customer satisfaction requirements? | | | Y | 100 | 100 |
| 9. | Is there a supplier certification program or equivalent procured material/service continuous quality improvement program? | | | Y | 50 | 50 |
| 10. | Can all personnel who contract suppliers properly reflect appropriate quality improvement programs and status to them? | | | Y | 100 | 100 |

COMMENTS

| |
|--|
| |
|--|

| 5.9 CALIBRATION CONTROL | | STATUS | | | | |
|--------------------------------|---|----------------|-------------|--------------------|------------------|-----------------|
| DESCRIPTION OF PROGRAM | | Not Applicable | Not Started | Approach Developed | Percent Deployed | Percent Results |
| 1. | Are calibration and preventative maintenance programs in place and documented? | | | Y | 100 | 100 |
| 2. | Are calibration and maintenance personnel trained? | | | Y | 100 | 100 |
| 3. | Is traceability to NIST maintained? | | | Y | 100 | 100 |
| 4. | Is quality measurement and control equipment current, effective, and sufficiently integrated with production equipment? | | | Y | 100 | 100 |
| 5. | Is the history of quality measurement and control equipment documented? | | | Y | 100 | 100 |
| 6. | Has repeatability of measuring devices and inspection or testing processes been established and monitored; are gauge capability studies conducted and GR&R ratios acceptable(<10%)? | | | Y | 100 | 100 |
| 7. | Are calibration and preventative maintenance cycles on schedule? | | | Y | 100 | 100 |
| 8. | Is the use of non-calibrated equipment for design and production purposes prohibited? | | | Y | 100 | 100 |
| 9. | Are tools and fixtures used as criteria or acceptability of product/work fully qualified and identified? | | | Y | 100 | 100 |
| 10. | Are calibration intervals defined in accordance with industry standards or manufacturer's recommendations and the calibration history of the equipment? | | | Y | 100 | 100 |

| 5.10 INTERNAL AUDITS | | STATUS | | | | |
|-----------------------------|--|----------------|-------------|--------------------|------------------|-----------------|
| DESCRIPTION OF PROGRAM | | Not Applicable | Not Started | Approach Developed | Percent Deployed | Percent Results |
| 1. | Are regular reviews of the product/process conducted and are goals/plans established to continually improve? | | | Y | 100 | 100 |
| 2. | Are the processes/products properly documented and controlled? Do they include appropriate customer requirements and are they executed in conformance to the documentation? | | | Y | 100 | 100 |
| 3. | Are the required quality checks built into the operations within the manufacturing, field installation, and service process, and is the resulting data maintained and promptly acted upon? | | | Y | 100 | 100 |
| 4. | Are all pertinent methods of statistical quality control properly, effectively and efficiently used? | | | Y | 100 | 100 |
| 5. | Does a process change control system exist, and are customers informed of changes made to products and processes with customer approval prior to the change, when required? | | | Y | 100 | 100 |
| 6. | Are the operators within the process provided with written work instructions and are they trained? | | | Y | 100 | 100 |
| 7. | Is the receipt, handling, storage, packaging and release of all material, including customer provided items, at all stages, specified and controlled to prevent damage or deterioration, and to address obsolete material? | | | Y | 100 | 100 |
| 1 | Is there a first in/first out (FIFO) system in place, and is it followed? | | | Y | 100 | 100 |

| COMMENTS |
|-----------------|
| |

| 5.11 STATISTICAL PROCESS CONTROL | | STATUS | | | | |
|----------------------------------|--|----------------|-------------|--------------------|------------------|-----------------|
| | | Not Applicable | Not Started | Approach Developed | Percent Deployed | Percent Results |
| DESCRIPTION OF PROGRAM | | | | | | |
| 1. | Have the personnel who will be responsible for guiding the implementation of SPC been designated? | | | Y | 100 | 100 |
| 2. | Are statistical techniques used to reduce variation in the engineering process before the start of production? | | | Y | 100 | 100 |
| 3. | Is the quality system dependent upon process rather than product controls? | | | Y | 90 | 90 |
| 4. | Is the capability of critical processes and machines measured and monitored with CPK's >1.5, and targeted with CP of 2.0? | | | Y | 50 | 40 |
| 5. | Are incapable processes or machines targeted for improvement or replacement? | | | Y | 100 | 100 |
| 6. | Is SPC implemented for all critical processes? | | | Y | 50 | 50 |
| 7. | Are procedures that control the reaction to out-of-control situations adequate and effective? | | | Y | 100 | 100 |
| 8. | Are operators trained in the use of appropriate statistical techniques, and are they properly applying them? | | | Y | 50 | 50 |
| 9. | Are advanced problem solving techniques used by engineers to solve problems? (Design of Experiments, planned experimentation, advanced diagnostic tools, etc.) | | | Y | 100 | 100 |
| 10. | Are control charts and other process controls properly implemented? | | | Y | 100 | 100 |
| 11. | Is statistical process control being practiced in work centers and are yields being recorded and plotted on a scheduled basis, with respect to upper and lower control limits? | | | Y | 50 | 50 |

| 5.12 PROBLEM SOLVING | | STATUS | | | | |
|------------------------|---|----------------|-------------|--------------------|------------------|-----------------|
| | | Not Applicable | Not Started | Approach Developed | Percent Deployed | Percent Results |
| DESCRIPTION OF PROGRAM | | | | | | |
| 1. | Are employees trained in problem solving techniques, in comparison to the needs of the organization? | | | Y | 90 | 90 |
| 2. | Does the organization utilize participative problem solving techniques to identify, measure and resolve internal and external problems? | | | Y | 100 | 100 |
| 3. | Are problem solving efforts timely and effective? | | | Y | 100 | 100 |
| 4. | Are applied resources sufficient to remove problem solving constraints? | | | Y | 100 | 100 |
| 5. | Are statistical techniques used for problem solving? | | | Y | 100 | 100 |
| 6. | Are quality data used to identify barriers, and to determine the priority of problems? | | | Y | 100 | 100 |
| 7. | Is there a policy/procedure that includes the use of problem solving techniques to systematically drive reduction in variability? | | | Y | 100 | 100 |

| COMMENTS | |
|----------|--|
| | |

| 5.13 IN-PROCESS CONTROL | | STATUS | | | | |
|-------------------------|--|----------------|-------------|--------------------|------------------|-----------------|
| | | Not Applicable | Not Started | Approach Developed | Percent Deployed | Percent Results |
| DESCRIPTION OF PROGRAM | | | | | | |
| 1. | Are process capabilities established and maintained on all major processes? (critical parameters) | | | Y | 100 | 100 |
| 2. | Are in-process inspections, test operations, and processes properly specified and performed? | | | Y | 100 | 100 |
| 3. | Are in-process inspection facilities and equipment adequate? | | | Y | 100 | 100 |
| 4. | Are the results of in-process inspections used in the promotion of effective preventative action and corrective action? | | | Y | 100 | 100 |
| 5. | Is preventative maintenance performed on the equipment and facilities? | | | Y | 100 | 100 |
| 6. | Are housekeeping procedures adequate and how well are they followed? | | | Y | 100 | 100 |
| 7. | Are process management plans established, and are critical parameters followed? | | | Y | 100 | 100 |
| 8. | Are work areas uncluttered and free of excess work-in-process, supplies, debris, etc? Is the environment conducive to producing quality work? Is proprietary information adequately protected? | | | Y | 100 | 100 |
| 9. | Are certifications and in-process inspection results used in making final acceptance decisions? | | | Y | 100 | 100 |
| 10. | Are methods and procedures for the control of metallurgical, chemical, and other special processes established and followed? | | | Y | 100 | 100 |

| 5.14 RECEIVING INSPECTION | | STATUS | | | | |
|---------------------------|---|----------------|-------------|--------------------|------------------|-----------------|
| | | Not Applicable | Not Started | Approach Developed | Percent Deployed | Percent Results |
| DESCRIPTION OF PROGRAM | | | | | | |
| 1. | Are receiving inspection facilities and equipment adequately and properly maintained? | | | Y | 100 | 100 |
| 2. | Are receiving inspection procedures documented and followed? | | | Y | 100 | 100 |
| 3. | Are receiving inspection results used for corrective and preventive action? | | | Y | 100 | 100 |
| 4. | Are the procedures for storage and timely disposition of discrepant material in place and followed? | | | Y | 100 | 100 |

| COMMENTS | | | | | |
|----------|--|--|--|--|--|
| | | | | | |

| 5.15 MATERIAL HANDLING | | STATUS | | | | |
|-------------------------------|---|----------------|-------------|--------------------|------------------|-----------------|
| DESCRIPTION OF PROGRAM | | Not Applicable | Not Started | Approach Developed | Percent Deployed | Percent Results |
| 1. | Are procured material releases from receiving inspection clearly identified, as to acceptance status? | | | Y | 100 | 100 |
| 2. | Are procedures to facilitate limited life materials, such as prepreg, in place, properly controlled, and monitored? | | | Y | 100 | 100 |
| 3. | Are procured items identified with some means of traceability (serial number, lot number, date code, etc.)? | | | Y | 100 | 100 |
| 4. | Are procedures and facilities adequate for storage, release and control of materials? | | | Y | 100 | 100 |
| 5. | Are in-store and in-process materials properly identified and controlled? | | | Y | 100 | 100 |
| 6. | Is in-process material protected from corrosion, deterioration, and damage? | | | Y | 100 | 100 |

| 5.16 NON-CONFORMING MATERIAL CONTROL | | STATUS | | | | |
|---|---|----------------|-------------|--------------------|------------------|-----------------|
| DESCRIPTION OF PROGRAM | | Not Applicable | Not Started | Approach Developed | Percent Deployed | Percent Results |
| 1. | Is non-conforming material identified, segregated from regular production material, and properly dispositioned? | | | Y | 100 | 100 |
| 2. | Are non-conforming materials properly identified and controlled to prevent inadvertent use? | | | Y | 100 | 100 |
| 3. | Is the review and disposition of non-conforming materials defined, and are provisions made for inclusion of the customer in disposition decision? | | | Y | 100 | 100 |
| 4. | Are procedures for controlling non-conforming materials, and for ensuing corrective action, in place and followed? | | | Y | 100 | 100 |
| 5. | Do procedures provide for material review by a committee consisting of Quality and Engineering (as a minimum), to determine the disposition of non-conforming materials? (deviating from drawings or specification) | | | Y | 100 | 100 |
| 6. | Do supplier's procedures and controls for corrective action prevent recurrence of non-conformances? | | | Y | 100 | 100 |
| 7. | Is there a system for coordinating necessary corrective action with purchasing personnel? | | | Y | 100 | 100 |
| 8. | Does the corrective action extend to all applicable causes of non-conformance (e.g., design, workmanship, procedures, equipment, etc.)? | | | Y | 100 | 100 |

| COMMENTS | |
|-----------------|--|
| | |

| 5.17 INSPECTION AND TEST PLAN | | STATUS | | | | |
|-------------------------------|--|----------------|-------------|--------------------|------------------|-----------------|
| | | Not Applicable | Not Started | Approach Developed | Percent Deployed | Percent Results |
| DESCRIPTION OF PROGRAM | | | | | | |
| 1. | Are statistical techniques used in determining the acceptability of finished goods to customer requirements? | | | Y | 100 | 100 |
| 2. | Are periodic tests conducted to audit reliability and environmental performance of the final product? | N/A | | | | |
| 3. | Is CPK tracking performed for critical characteristics, with plans to achieve CPK = 1.5 with a target of CP of 2.0? | | X | | | |
| 4. | Is root cause failure analysis performed for internal and external failures, and is appropriate corrective action implemented? | | | Y | 100 | 100 |
| 5. | Are test and inspection personnel trained in the procedures of their operations, and are those procedures being followed? | | | Y | 100 | 100 |
| 6. | Is the new product/technology/service, as produced by the processes, verified to meet all customer satisfaction requirements? | | | Y | 100 | 100 |

| 5.18 PRODUCT INSPECTION/FINAL AUDIT | | STATUS | | | | |
|-------------------------------------|--|----------------|-------------|--------------------|------------------|-----------------|
| | | Not Applicable | Not Started | Approach Developed | Percent Deployed | Percent Results |
| DESCRIPTION OF PROGRAM | | | | | | |
| 1. | Are final product acceptance procedures documented and followed? | | | Y | 100 | 100 |
| 2. | Are all specific customer product audits conducted, as required? | | | Y | 100 | 100 |
| 3. | Are inspectors trained for the tasks performed? | | | Y | 100 | 100 |
| 4. | Are flow charts or milestones developed with checkpoints readily available? | | | Y | 100 | 100 |
| 5. | Is a system in place which denotes inspection performed; e.g., use of initials, stamps, labels, bar codes, etc., affixed to production documentation? | | | Y | 100 | 100 |
| 6. | Is a quality system established and maintained for control of product/production documentation? | | | Y | 100 | 100 |
| 7. | Is "accept/reject" criteria defined and available for use? | | | Y | 100 | 100 |
| 8. | Is a final audit performed to ensure that all required verifications and tests, from receipt of materials through point of product completion, have been accomplished? | | | Y | 100 | 100 |
| 9. | Are packing and order checking procedures documented and followed? | | | Y | 100 | 100 |

| COMMENTS | |
|----------|--|
| | |

| 5.19 TOOLING INSPECTION, HANDLING, & STORAGE | | STATUS | | | | |
|--|---|----------------|-------------|--------------------|------------------|-----------------|
| | | Not Applicable | Not Started | Approach Developed | Percent Deployed | Percent Results |
| DESCRIPTION OF PROGRAM | | | | | | |
| 1. | Are temperature, humidity, laminar flow controls in place to prevent contamination, and to assure dimensional stability? | | | Y | 100 | 100 |
| 2. | Do operators use hairnets, gloves & lab coats in all photolab and photoexposure areas? | | | Y | 100 | 100 |
| 3. | Are work instructions and related forms in place to control all applicable tooling requirements, as stated in the customer's purchase order? | | | Y | 100 | 100 |
| 4. | Are customer provided artworks controlled with regard to handling, storage, revision control and relationship to converted production phototools (working films)? | | | Y | 100 | 100 |
| 5. | Are production phototools (working films) controlled with regard to handling, storage, use life, and relationship to customer purchase order? | | | Y | 100 | 100 |
| 6. | Are customer provided artworks and production phototools (working films) inspected, including dimensional checks? | | | Y | 100 | 100 |
| 7. | Are all tools, fixtures, and other devices, used for tooling inspection and control, maintained under the calibration control procedure? | | | Y | 100 | 100 |
| 8. | Are records showing initial acceptance, periodic checks, and any needs for rework and/or modification available? | | | Y | 100 | 100 |

| 5.20 CORRECTIVE ACTION | | STATUS | | | | |
|------------------------|---|----------------|-------------|--------------------|------------------|-----------------|
| | | Not Applicable | Not Started | Approach Developed | Percent Deployed | Percent Results |
| DESCRIPTION OF PROGRAM | | | | | | |
| 1. | Are final acceptance inspection results used for corrective and preventative action? | | | Y | 100 | 100 |
| 2. | Is root-cause analysis performed for non-conformances? This includes, but is not limited to, non-conformances (problems) caused by suppliers, found/caused "in-house" during processing, or those reported by the customer. | | | Y | 100 | 100 |
| 3. | Is positive action taken to prevent recurrence of problems, and are there documented reports/records of each occasion? | | | Y | 100 | 100 |
| 4. | Do procedures and systems provide for ensuring that replies are made to customer requests for correction action within the time limit specified? | | | Y | 100 | 100 |
| 5. | Is corrective action controlled and documented for all applicable work centers? | | | Y | 100 | 100 |
| 6. | When corrections are made, is their effectiveness subsequently reviewed and monitored? | | | Y | 100 | 100 |

| COMMENTS | | | | | | |
|----------|--|--|--|--|--|--|
| | | | | | | |

SECTION 6 (CHECK ONE IN EACH LINE THAT APPLIES)

MANUFACTURING HISTORY (See Section 2 Site Capability)

| |
|------------------------------|
| DATE COMPLETED 10/27/2016 |
|------------------------------|

Please complete as many history profiles so that the total descriptions of products you manufacture account for production orders that reflect 70% of your business. History profiles are for board or board family (board types may be grounded together if they are similar).

| | | | |
|-----------------------|------------------------------|----------------------------------|----------------------|
| BOARD TYPE Rigid | DATE OF ORDER 2009 | MATERIAL Fr4 | HISTORY # Average |
| VIA TYPE Thru hole | PRODUCTION QUANTITY 18000 | TOTAL YEARLY PRODUCTION % 70% | |

Dimensions in millimeters (inches in brackets)

| BOARD | | | HOLES | | |
|---|--|---|---|--|---|
| BOARD SIZE DIAGONAL | TOTAL BOARD THICKNESS | NUMBER CONDUCTIVE LAYERS | DIA DRILLED HOLES | TOTAL PTH TOL (MAX-MIN) | LOCATION TOL DTP |
| <input type="checkbox"/> <250 [<10.00] | <input type="checkbox"/> <1,0 [<.040] | <input type="checkbox"/> 1-4 [1-4] | <input type="checkbox"/> >0,5 [>.020] | <input type="checkbox"/> >0,250 [>.010] | <input type="checkbox"/> >0,50 [>.020] |
| <input type="checkbox"/> 250 [10.00] | <input type="checkbox"/> 1,0 [.040] | <input type="checkbox"/> 5-6 [5-6] | <input type="checkbox"/> 0,5 [.020] | <input type="checkbox"/> 0,250 [.010] | <input type="checkbox"/> 0,50 [.020] |
| <input type="checkbox"/> 350 [14.00] | <input type="checkbox"/> 1,6 [.060] | <input type="checkbox"/> 7-8 [7-8] | <input type="checkbox"/> 0,4 [.016] | <input type="checkbox"/> 0,200 [.008] | <input type="checkbox"/> 0,40 [.016] |
| <input type="checkbox"/> 450 [17.50] | <input checked="" type="checkbox"/> 2,0 [.080] | <input checked="" type="checkbox"/> 9-12 [9-12] | <input type="checkbox"/> 0,35 [.014] | <input type="checkbox"/> 0,150 [.006] | <input type="checkbox"/> 0,30 [.012] |
| <input checked="" type="checkbox"/> 550 [21.50] | <input type="checkbox"/> 2,5 [.100] | <input type="checkbox"/> 13-16 [13-16] | <input type="checkbox"/> 0,30 [.012] | <input type="checkbox"/> 0,125 [.005] | <input type="checkbox"/> 0,25 [.010] |
| <input type="checkbox"/> 650 [25.50] | <input type="checkbox"/> 3,5 [.135] | <input type="checkbox"/> 17-20 [17-20] | <input type="checkbox"/> 0,25 [.010] | <input type="checkbox"/> 0,100 [.004] | <input type="checkbox"/> 0,20 [.008] |
| <input type="checkbox"/> 750 [29.50] | <input type="checkbox"/> 5,0 [.200] | <input type="checkbox"/> 21-24 [21-24] | <input checked="" type="checkbox"/> 0,20 [.008] | <input checked="" type="checkbox"/> 0,075 [.003] | <input type="checkbox"/> 0,15 [.006] |
| <input type="checkbox"/> 850 [33.50] | <input type="checkbox"/> 6,5 [.250] | <input type="checkbox"/> 25-28 [25-28] | <input type="checkbox"/> 0,15 [.006] | <input type="checkbox"/> 0,050 [.002] | <input checked="" type="checkbox"/> 0,10 [.004] |
| <input type="checkbox"/> >850 [>33.50] | <input type="checkbox"/> >6,5 [>.250] | <input type="checkbox"/> >28 [>28] | <input type="checkbox"/> <0,15 [<.006] | <input type="checkbox"/> <0,050 [<.002] | <input type="checkbox"/> <0,10 [<.004] |
| <input type="checkbox"/> Other: | <input type="checkbox"/> Other: | <input type="checkbox"/> Other: | <input type="checkbox"/> Other: | <input type="checkbox"/> Other: | <input type="checkbox"/> Other: |

CONDUCTORS

| INTERNAL ELEC CLEARANCE (MIN) | INTERNAL COND WIDTH (MIN) | INTERNAL PROCESS ALLOWANCE | EXTERNAL ELEC CLEARANCE (MIN) | EXTERNAL COND WIDTH (MIN) | EXTERNAL PROCESS ALLOWANCE | FEATURE LOCATION DTP |
|--|--|--|--|--|--|---|
| <input type="checkbox"/> >0,350 [>.014] | <input type="checkbox"/> >0,250 [>.010] | <input type="checkbox"/> >0,100 [>.004] | <input type="checkbox"/> >0,350 [>.014] | <input type="checkbox"/> >0,250 [>.010] | <input type="checkbox"/> >0,100 [>.004] | <input type="checkbox"/> >0,50 [>.020] |
| <input type="checkbox"/> 0,350 [.014] | <input type="checkbox"/> 0,250 [.010] | <input type="checkbox"/> 0,100 [.004] | <input type="checkbox"/> 0,350 [.014] | <input type="checkbox"/> 0,250 [.010] | <input type="checkbox"/> 0,100 [.004] | <input type="checkbox"/> 0,50 [.020] |
| <input type="checkbox"/> 0,250 [.010] | <input type="checkbox"/> 0,200 [.008] | <input type="checkbox"/> 0,075 [.003] | <input type="checkbox"/> 0,250 [.010] | <input type="checkbox"/> 0,200 [.008] | <input type="checkbox"/> 0,075 [.003] | <input type="checkbox"/> 0,40 [.016] |
| <input type="checkbox"/> 0,200 [.008] | <input type="checkbox"/> 0,150 [.006] | <input type="checkbox"/> 0,050 [.002] | <input type="checkbox"/> 0,200 [.008] | <input type="checkbox"/> 0,150 [.006] | <input type="checkbox"/> 0,050 [.002] | <input type="checkbox"/> 0,30 [.012] |
| <input checked="" type="checkbox"/> 0,150 [.005] | <input type="checkbox"/> 0,125 [.005] | <input type="checkbox"/> 0,040 [.0015] | <input type="checkbox"/> 0,150 [.006] | <input checked="" type="checkbox"/> 0,125 [.005] | <input type="checkbox"/> 0,040 [.0015] | <input type="checkbox"/> 0,25 [.010] |
| <input type="checkbox"/> 0,125 [.005] | <input checked="" type="checkbox"/> 0,100 [.004] | <input type="checkbox"/> 0,030 [.0012] | <input type="checkbox"/> 0,125 [.005] | <input type="checkbox"/> 0,100 [.004] | <input type="checkbox"/> 0,030 [.0012] | <input type="checkbox"/> 0,20 [.008] |
| <input type="checkbox"/> 0,100 [.004] | <input type="checkbox"/> 0,075 [.003] | <input checked="" type="checkbox"/> 0,025 [.001] | <input checked="" type="checkbox"/> 0,100 [.004] | <input type="checkbox"/> 0,075 [.003] | <input checked="" type="checkbox"/> 0,025 [.001] | <input type="checkbox"/> 0,15 [.006] |
| <input type="checkbox"/> 0,075 [.003] | <input type="checkbox"/> 0,050 [.002] | <input type="checkbox"/> 0,020 [.0008] | <input type="checkbox"/> 0,075 [.003] | <input type="checkbox"/> 0,050 [.002] | <input type="checkbox"/> 0,020 [.0008] | <input checked="" type="checkbox"/> 0,10 [.004] |
| <input type="checkbox"/> <0,075 [<.003] | <input type="checkbox"/> <0,050 [<.002] | <input type="checkbox"/> <0,020 [<.0008] | <input type="checkbox"/> <0,075 [<.003] | <input type="checkbox"/> <0,050 [<.002] | <input type="checkbox"/> <0,020 [<.0008] | <input type="checkbox"/> <0,10 [<.004] |
| <input type="checkbox"/> Other: | <input type="checkbox"/> Other: | <input type="checkbox"/> Other: | <input type="checkbox"/> Other: | <input type="checkbox"/> Other: | <input type="checkbox"/> Other: | <input type="checkbox"/> Other: |

SECTION 7

| |
|------------------------------|
| DATE COMPLETED 10/27/2016 |
|------------------------------|

IDENTIFICATION OF PREVIOUS AUDITS (Optional)

Please complete as many forms as you feel reflect the intensity of your customer visits.

| | |
|--|--|
| COMPANY AUDITORS SAI Global, Inc. | DATE OF AUDIT 9/10/2016 (4 Day Audit) |
| AUDIT TEAM MEMBERS | AUDITOR REMARKS Pass |
| | SPECIFICATIONS USED IN AUDIT AS9100 Rev. C - ISO 9001:2008 Standard |
| LENGHT OF AUDIT 4 Days | |
| TEAM MEMBERS MAY BE CONTACTED AT 216-654-0900 | |

| | |
|---|--|
| COMPANY AUDITORS Ashok Patel | DATE OF AUDIT Continuous |
| AUDIT TEAM MEMBERS Juan Rubio Jay Savalia | AUDITOR REMARKS |
| | SPECIFICATIONS USED IN AUDIT AS9100 Rev. C - ISO 9001:2008 Standard |
| LENGHT OF AUDIT Internal audit are performed Quartly . | |
| TEAM MEMBERS MAY BE CONTACTED AT 972-790-0062 | |

| | |
|--------------------------------|------------------------------|
| COMPANY AUDITORS | DATE OF AUDIT |
| AUDIT TEAM MEMBERS | AUDITOR REMARKS |
| | SPECIFICATIONS USED IN AUDIT |
| LENGHT OF AUDIT | |
| TEAM MEMBERS MAY BE CONTACT AT | |

*REPEAT THIS FORM AS NECESSARY

SECTION 8

| |
|------------------------------|
| DATE COMPLETED 10/27/2016 |
|------------------------------|

FINANCIAL REVIEW (OPTIONAL)

Please complete the following financial information that coincides with the company description and site information provided in section 1.

COMPANY FINANCIAL DESCRIPTION

| | | |
|--|--------------------------|-----------------------|
| LEGAL NAME Multilayer Technology | | |
| TAXPAYER ID NUMBER 1-75-2147237 | DUNS NUMBER 118647882 | TRADING SYMBOL N/A |
| ANNUAL SALES | PRIOR YEAR | YEAR-TO-DATE |
| FISCAL YEAR Ending December | | |
| BANK | ACCOUNT NUMBER | |
| BANK ADDRESS | STATE | ZIP |
| PROVINCE | COUNTRY | |
| BANK TELEPHONE NUMBER | FAX NUMBER | |
| COMMENTS ** Any financial request has to be submitted to the President of Multilayer Technology. A NDA will be required prior to release. | | |

SITE FINANCIAL DESCRIPTION

| | | |
|-----------------------|----------------|----------------|
| SITE NAME | | |
| TAXPAYER ID NUMBER | DUNS NUMBER | TRADING SYMBOL |
| ANNUAL SALES | PRIOR YEAR | YEAR-TO-DATE |
| FISCAL YEAR | | |
| BANK | ACCOUNT NUMBER | |
| BANK ADDRESS | STATE | ZIP |
| PROVINCE | COUNTRY | |
| BANK TELEPHONE NUMBER | FAX NUMBER | |
| COMMENTS | | |

SECTION 9

MQP ELECTRONIC EDITING

This MS Word template comes with editable fields. IPC has made this electronic document available for ease of completing, updating, and filing the MQP, as well as to give the laminate manufacturer and customer a common interface. Using the template enables laminate manufacturers to maintain several customer specific files without the endless stream of paperwork.

Editable fields are highlighted in gray. To complete the fields in the template, use the TAB key to toggle from field to field, entering the information as instructed in the introductory text for each section.

The developers of this MQP strongly suggest the person at the laminate manufacturing facility responsible for creating and maintaining the MQP write protect the file to be sent.